

LDA - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.25				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	3.40 NM AFTER KANAN LOM OR AT CCR 3.10 DME FIX CLIMB TO 900 THEN CLIMBING LEFT TURN TO 3500 DIRECT CCR VOR/DME; OR WHEN DIRECTED BY ATC, CLIMB TO 900 THEN CLIMBING LEFT TURN TO 2000 DIRECT C C LOM AND HOLD N, LT, 180.91 INBOUND. ADDITIONAL FLIGHT DATA: CHART FAS OBST: 128 TREE 375944N/1220256W CCR VOR/DME 2.00 DME TO RW19R: 3.09/28. CHART DISTANCE LOM TO 2 DME - 2.2 NM CHART DISTANCE 2 DME TO THLD - 1.2 NM											
COLLI INT	KANAN LOM	355.21 / 11.30	5100												
REJOY INT (IAF)	JOANS INT/CCR 8.13 DME (NOPT)	254.37 / 10.00 (SGD R-074)	2000												
JOANS INT/CCR 8.13 DME (IF)	KANAN LOM	180.76 / 7.90 (I-CCR)	1300												
1. PT <u>R</u> SIDE OF COURSE <u>000.76</u> OUTBOUND <u>2500</u> FT WITHIN <u>10</u> MILES OF <u>KANAN LOM</u> (IAF) 2. _____ 3. FAC: <u>180.76</u> FAF: <u>KANAN LOM</u> DIST FAF TO MAP: <u>3.36</u> THLD: <u>3.36</u> 4. MIN. ALT: <u>KANAN LOM 1300, CCR 2.00 DME 440</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.09</u> TCH: <u>28.0</u> 8. MSA FROM: <u>CCR VOR/DME 360-090 3100, 090-180 5100, 180-360 4100</u>				MAG VAR: <u>17E</u> EPOCH YEAR: <u>1980</u>											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: <u>N A</u>											
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-19R	440	3/4	418	440	3/4	418	440	1 1/4	418		NA				
CIRCLING	600	1	574	680	1	654	680	1 3/4	654		NA				
DME MINIMUMS															
S-19R	380	3/4	358	380	3/4	358	380	3/4	358		NA				
CIRCLING	600	1	574	680	1	654	680	1 3/4	654		NA				
NOTES: CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO CAT C. CHART PROFILE NOTE: VGSi AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED CHART NOTE: CIRCLING NA WEST OF RWY 1L-19R															
CITY AND STATE CONCORD, CA		ELEVATION: 26 TDZE: 22 AIRPORT NAME: BUCHANAN FIELD		FACILITY IDENTIFIER: I-CCR		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: LDA RWY 19R, AMDT 7E 15 SEPTEMBER 2016				SUP: AMDT: 7D DATED 06/26/2014					

