

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: PWC NDB						
PKD VOR/DME		PWC NDB			105.71 / 30.07			3200		CLIMB TO 3100 THEN RIGHT TURN DIRECT PWC NDB AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD S, RT, 340.49 INBOUND. CHART FAS OBST: 1720 TOWER 463656N/0941818W FAC 498 FT L OF RWY C/L EXTENDED 3000 FT FROM THLD.						
1. PT <u>L</u> SIDE OF COURSE <u>160.49</u> OUTBOUND <u>3100</u> FT WITHIN <u>10</u> MILES OF <u>PWC NDB</u> (IAF)																
2.																
3. FAC <u>340.49</u> FAF _____ DIST FAF TO MAP _____ THLD _____																
4. MIN. ALT _____																
8. MSA FROM: PWC NDB 3400										MAG VAR: 3E EPOCH YEAR: 2000						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N		A		X					
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-34	2080	1	784	2080	1 1/4	784	2080	2 1/2	784		NA					
CIRCLING	2080	1	784	2080	1 1/4	784	2080	2 1/2	784		NA					
NOTES:																
CHART NOTE: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.																
CITY AND STATE PINE RIVER, MN		ELEVATION: 1296 TDZE: 1296 AIRPORT NAME: PINE RIVER RGNL			FACILITY IDENTIFIER: PWC		PROCEDURE NO./AMD'T NO./EFFECTIVE DATE: NDB RWY 34, AMDT 1A 17 AUGUST 2017					SUP AMD'T 1 DATE 11/30/2000				

