

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 2600 DIRECT UYUPU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 178.29 INBOUND. CHART FAS OBST: 914 TREE 370845N/0954600W. DISTANCE TO THLD FROM 200 HAT: 0.50 NM. CHART VDP AT 0.99 NM TO RW35* *LNAV ONLY. WAAS CHANNEL # 53310 REFERENCE PATH ID: W35A CHART CIRCLING ICON. CHART EUREKA LOW MOA. LTP HAE: 219.9 M									
BVO VOR/DME		WARTO (TF) (FB) (RNP 2.00)		035.50 / 8.99				2600											
WARTO (IAF)		USUCE (NOPT) (TF) (FB) (RNP 1.00)		086.21 / 6.10				2600											
EJYAR (IAF)		USUCE (NOPT) (TF) (FB) (RNP 1.00)		278.76 / 9.50				2600											
USUCE (IF/IAF)		ZIMID (TF) (FB) (RNP 1.00)		358.29 / 6.12				2600											
ZIMID (FAF)		YIRGU/2.80 NM TO RW35 (TF) (FB) (RNP 0.30)		358.29 / 2.66				2600											
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S USUCE, RT, 358.29 INBOUND, 2600 FT. IN LIEU OF PT (IAF) 3. FAC: 358.29 FAF: ZIMID DIST FAF TO MAP: 5.46 THLD: 5.46 4. MIN. ALT: USUCE 2600, ZIMID 2600, YIRGU/2.80 NM TO RW35 1740* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2600 GS ALT AT: ZIMID 2600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 42.2 34:1 IS CLEAR 8. MSA FROM: RW35 2800																MAG VAR: 2E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A		B		C		D		E									
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	1021	1/2	200	1021	1/2	200	1021	1/2	200	1021	1/2	200							
LNAV/VNAV DA	1097	1/2	276	1097	1/2	276	1097	1/2	276	1097	1/2	276							
LNAV MDA	1180	1/2	359	1180	1/2	359	1180	5/8	359	1180	5/8	359							
CIRCLING	1280	1	455	1280	1	455	1340	1 1/2	515	1680	2 3/4	855							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). @ CAT D 900-2 3/4 CHART NOTE: CIRCLING RWY 4, 22 NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT BVO VOR/DME ON V190 SOUTHWEST BOUND. (CONTINUED ON PAGE 2)																			
CITY AND STATE		ELEVATION: 825 TDZE: 821				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:							
INDEPENDENCE, KS		AIRPORT NAME:				RNAV		RNAV (GPS) RWY 35, AMDT 1				AMDT: ORIG							
		INDEPENDENCE MUNI						1 FEBRUARY 2018				DATED 11/20/2008							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
YIRGU/2.80 NM TO RW35	RW35 (MAP) (TF) (FO) (RNP 0.30)	358.29 / 2.80	
RW35 (MAP)	1021 MSL (CA)	358.29	
1021 MSL	UYUPU (DF) (FO) (RNP 1.00)		2600

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EJYAR ON V190 NORTHEAST BOUND.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV DA ALL CATS VISIBILITIES TO 7/8 SM AND LNAV MDA CATS C AND D VISIBILITIES TO 1 SM.

QUALITY
16
CHECKED

CITY AND STATE

INDEPENDENCE, KS

ELEVATION: 825

TDZE: 821

AIRPORT NAME:

INDEPENDENCE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, AMDT 1

1 FEBRUARY 2018

SUP:

AMDT: **ORIG**

DATED: **11/20/2008**

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE INDEPENDENCE, KS	ELEVATION: 825	TDZE: 821	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 1 FEBRUARY 2018	SUP:
	AIRPORT NAME:				AMDT: ORIG
	INDEPENDENCE MUNI				DATED: 11/20/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIDP
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	370858.6375N
LTP/FTP LONGITUDE	0954635.9380W
LTP/FTP ELLIPSOIDAL HEIGHT	+02199
FPAP LATITUDE	371027.8480N
FPAP LONGITUDE	0954635.3740W
THRESHOLD CROSSING HEIGHT (TCH)	00042.2
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1072
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 9FC11B87

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02498
FPAP ORTHOMETRIC HEIGHT	+02498

QUALITY
16
CHECKED

CITY AND STATE INDEPENDENCE, KS	ELEVATION: 825 TDZE: 821 AIRPORT NAME: INDEPENDENCE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 1 FEBRUARY 2018	SUP:
				AMDT: ORIG
				DATED: 11/20/2008