

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and FIA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTE										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 4.81 MILES AFTER MFD VORTAC OR AT MFD 4.81 DME CLIMB TO 3000 VIA HEADING 290 AND MFD R-279 TO ZISKI INT/MFD 10.00 DME AND HOLD ADDITIONAL FLIGHT DATA: HOLD W, RT, 098.99 INBOUND FAS OBST: 1295 STACK 405246/823924							
1. PT <u>L</u> SIDE OF COURSE <u>095.57</u> OUTBOUND <u>2900</u> FT WITHIN <u>10</u> MILES OF <u>MFD VORTAC</u> (IAF) 2. _____ 3. FAC <u>275.57</u> FAF <u>MFD VORTAC</u> DIST FAF TO MAP <u>4.81</u> THLD <u>-</u> 4. MIN. ALT <u>MFD VORTAC 2600</u> 8. MSA FROM: <u>MDF VORTAC 3000</u>														MAG VAR: 3W		EPOCH YEAR: 65	
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		X					
CATEGORY ==>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
CIRCLING	1640	1	520	1640	1	520	1640	1 1/2	520		NA						
NOTES: USE MANSFIELD ALTIMETER SETTING 																	
CITY AND STATE				ELEVATION: 1120 TDZE:				FACILITY IDENTIFIER:				PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP	
SHELBY, OH				SHELBY COMMUNITY				MFD				SEP 4 2003 VOR-A, AMDT 5				AMDT 4A	
																DATE 10/30/98	