

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW36 CLIMB TO 2000 DIRECT BUCMU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 183.01 INBOUND. CHART FAS OBST: 322 TOWER 262343N/0812446W DISTANCE TO THLD FROM 250 HAT: 0.63 NM. CHART VDP AT 1.57 NM TO RW36* *LNAV ONLY. WAAS CHANNEL # 73013 REFERENCE PATH ID: W36A CHART CIRCLING ICON. LTP HAE: -14.3 M									
JIRAX (IAF)		DIBUF (NOPT) (TF) (FB) (RNP 1.00)			092.96 / 7.70			2300											
ZAWRI (IAF)		DIBUF (NOPT) (TF) (FB) (RNP 1.00)			273.09 / 7.70			2300											
DIBUF (IF/IAF)		CAKNA (TF) (FB) (RNP 1.00)			003.02 / 6.02			1700											
CAKNA (FAF)		RW36 (MAP) (TF) (FO) (RNP 0.30)			003.02 / 5.08														
RW36 (MAP)		284 MSL (CA)			003.02			2000											
284 MSL		BUCMU (DF) (FO) (RNP 1.00)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD S DIBUF, RT, 003.02 INBOUND, 2300 FT. IN LIEU OF PT (IAF) 3. FAC: 003.02 FAF: CAKNA DIST FAF TO MAP: 5.08 THLD: 5.08 4. MIN. ALT: DIBUF 2300, CAKNA 1700 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1700 GS ALT AT: CAKNA 1700 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 50.0 34:1 IS CLEAR 8. MSA FROM: _____																MAG VAR: 5W		EPOCH YEAR: 2010	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD										
CATEGORY ==>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	284	3/4	250	284	3/4	250	284	3/4	250	284	3/4	250							
LNAV/VNAV DA	284	3/4	250	284	3/4	250	284	3/4	250	284	3/4	250							
LNAV MDA	580	1	546	580	1	546	580	1 5/8	546	580	1 5/8	546							
CIRCLING																			
	580	1	543	640	1	603	640	1 3/4	603	680	2	643							
NOTES:																			
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW 0C (32F) OR ABOVE 54C (130F).																			
CHART NOTE: DME/DME RNP-0.3 NA.																			
CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).																			
CITY AND STATE		ELEVATION: 37 TDZE: 34			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:					SUP:						
IMMOKALEE, FL		AIRPORT NAME: IMMOKALEE RGNL						RNAV (GPS) RWY 36, AMDT 1					AMDT: ORIG-C						
								17 AUGUST 2017					DATED 10/16/2014						

QUALITY
 10
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	273/30 CW 093/30 (NOPT)	DIBUF (IF/IAF) (FB)	2300
2.	093/30 CW 183/30	JIRAX (IAF) (FB)	2300
3.	183/30 CW 273/30	ZAWRI (IAF) (FB)	2300

CITY AND STATE
IMMOKALEE, FL

ELEVATION: 37 TDZE: 34
AIRPORT NAME:
IMMOKALEE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 36, AMDT 1
17 AUGUST 2017

SUP: **QUALITY
10
CHECKED**
AMDT: **ORIG-C**
DATED: **10/16/2014**

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE IMMOKALEE, FL	ELEVATION: 37 AIRPORT NAME: IMMOKALEE RGNL	TDZE: 34	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 17 AUGUST 2017	SUP:
					AMDT: ORIG-C
					DATED: 10/16/2014

QUALITY
10
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KIMM
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	262524.6015N
LTP/FTP LONGITUDE	0812416.8795W
LTP/FTP ELLIPSOIDAL HEIGHT	-00143
FPAP LATITUDE	262653.9100N
FPAP LONGITUDE	0812420.3100W
THRESHOLD CROSSING HEIGHT (TCH)	00050.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1368
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

CE309781

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00101
FPAP ORTHOMETRIC HEIGHT	+00101

QUALITY
10
CHECKED

CITY AND STATE

IMMOKALEE, FL

ELEVATION: 37

TDZE: 34

AIRPORT NAME:

IMMOKALEE RGNL

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, AMDT 1

17 AUGUST 2017

SUP:

AMDT:

DATED:

ORIG-C

10/16/2014