

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: AIK NDB					
IRQ VORTAC CAE VORTAC		AIK NDB		101.67 / 24.51				2400		CLIMBING RIGHT TURN TO 2200 IN AIK NDB HOLDING PATTERN.					
		AIK NDB		250.64 / 33.51				2200							
ADDITIONAL FLIGHT DATA: HOLD NE, RT, 224.52 INBOUND. CHART FAS OBST: 830 TREE 334712N/08113454W FAC CROSSES RWY C/L EXTENDED 3003 FROM THLD.															
1. PT <u> L </u> SIDE OF COURSE <u> 044.52 </u> OUTBOUND <u> 2200 </u> FT WITHIN <u> 10 </u> MILES OF <u> AIK NDB </u> (IAF)															
2. _____															
3. FAC <u> 224.52 </u> FAF _____ DIST FAF TO MAP _____ THLD _____															
4. MIN. ALT _____															
8. MSA FROM: AIK NDB 3000															
MINIMUMS TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A X															
CATEGORY ==>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-25	1180	3/4	686	1180	3/4	686	1180	1 7/8	686	1180	1 7/8	686			
CIRCLING	1180	1	652	1180	1	652	1180	2	652	1180	2	652			
NOTES: CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO CAT C/D WHEN USING AUGUSTA RGNL AT BUSH FIELD ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AUGUSTA RGNL AT BUSH FIELD ALTIMETER SETTING AND INCREASE ALL MDA 120 FEET AND INCREASE S-25 AND CIRLING CAT B VISIBILITY TO 1, CAT (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 528 THRE: 494		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP					
AIKEN, SC		AIRPORT NAME:		AIK		NDB RWY 25, AMDT 10A				AMDT 10					
		AIKEN MUNI				15 DEC 2011				DATE 01/18/2007					



NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

C/D VISIBILITY TO 2 1/2.

CHART NOTE: FOR INOPERATIVE ODALS, INCREASE S-25 CAT C/D VISIBILITY TO 2.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.



CITY AND STATE AIKEN, SC	ELEVATION: 528	THRE: 494	FACILITY IDENTIFIER: AIK	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 25, AMDT 10A 15 DEC 2011	SUP:
	AIRPORT NAME: AIKEN MUNI	AMDT: 10			
	DATED: 01/18/2007				