

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: AHN VORTAC							
												CLIMB TO 2400 THEN LEFT TURN DIRECT AHN VORTAC AND HOLD.							
												ADDITIONAL FLIGHT DATA: HOLD S, RT, 015.00 INBOUND. FAS OBST: 1000 AAO 335648N/0831450W CHART VDP AT 1.75 DME DISTANCE VDP TO THLD 1.40 MILES. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 3010 FROM THLD.							
1. PT <u>R</u> SIDE OF COURSE <u>081.57</u> OUTBOUND <u>2400</u> FT WITHIN <u>10</u> MILES OF <u>AHN VORTAC</u> (IAF)																			
2.																			
3. FAC <u>261.57</u> FAF										DIST FAF TO MAP THLD									
4. MIN. ALT																			
8. MSA FROM: <u>AHN VORTAC 3700</u>										MAG VAR: <u>0E</u> EPOCH YEAR: <u>1965</u>									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: <u>N A</u>		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-27		1300	3/4	487	1300	3/4	487	1300	1 1/4	487	1300	1 1/4	487						
CIRCLING		1300	1	487	1300	1	487	1320	1 1/2	507	1460	2	647						
NOTES:																			
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WINDER ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND S-27 CATS C AND D VISIBILITY TO 1 3/8 MILE, CIRCLING CAT D VISIBILITY TO 2 1/4 MILES.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.									
CHART NOTE: VDP NA WHEN USING WINDER ALTIMETER SETTING. (SEE FORM 8260-10)																			
CITY AND STATE ATHENS, GA				ELEVATION: 813 TDZE: 813 AIRPORT NAME: ATHENS/BEN EPPS				FACILITY IDENTIFIER: AHN		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 27, AMDT 13 15 OCTOBER 2015						SUP AMDT 12A DATE 05/03/2012			



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: FOR INOPERATIVE ODALS, INCREASE S-27 CATS C,D VISIBILITY TO 1 3/8 MILE.****CHART NOTE: NIGHT LANDING: RWY 2, 20 NA.****CHART NOTE: FOR INOPERATIVE ODALS WHEN USING WINDER ALTIMETER SETTING, INCREASE S-27 CAT D
VISIBILITY TO 1 5/8 MILE.**

QUALITY
10
CHECKED

CITY AND STATE

ATHENS, GA

ELEVATION: 813**TDZE: 813**

AIRPORT NAME:

ATHENS/BEN EPPS

FACILITY
IDENTIFIER:

AHN

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 27, AMDT 13

15 OCTOBER 2015

SUP:

AMDT: 12A

DATED: 05/03/2012