

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.						
TERMINAL ROUTES														MISSED APPROACH						
FROM				TO			COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: I-ENF 1.75 DME							
OVR VORTAC (IAF)				BOCTA INT/I-ENF 9.32 DME (NOPT)			292.18 / 2.71				2800		CLIMB TO 1800 THEN CLIMBING RIGHT TURN TO 3000 DIRECT OVR VORTAC AND HOLD.							
BOCTA INT/I-ENF 9.32 DME (IF)				PONYS/I-ENF 7.30 DME			322.40 / 2.02 (I-ENF)				2800									
														ADDITIONAL FLIGHT DATA: HOLD E, RT, 284.00 INBOUND. CHART FAS OBST: 1173 ELEVATOR 411620N/0955135W. CHART VDP AT 3.03 DME* DISTANCE VDP TO THLD 1.28 NM. *LOC ONLY. CHART CIRCLING ICON.						
1. PT <u>L</u> SIDE OF COURSE <u>142.40</u> OUTBOUND <u>2800</u> FT WITHIN <u>10</u> MILES OF <u>PONYS</u> (IAF)														MAG VAR: 2E EPOCH YEAR: 2020						
2.																				
3. FAC: <u>322.40</u> FAF: <u>PONYS/I-ENF 7.30 DME</u> DIST FAF TO MAP: THLD: <u>5.55</u>																				
4. MIN. ALT: <u>PONYS/I-ENF 7.30 DME 2800, FAPON/I-ENF 3.85 DME 1700*</u>																				
5. DIST TO THLD FROM OM: - MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: <u>998</u>																				
6. MIN GS INCPT: <u>2800</u> GS ALT AT: <u>PONYS 2800</u> OM: - MM: - IM: -																				
7. GS ANGLE: <u>3.00</u> TCH: <u>52.2</u>																				
8. MSA FROM: <u>OVR VORTAC 4100</u>																				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		ILS: STANDARD LOC: STANDARD @											
CATEGORY =====>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
S-ILS 32L**	1181	2400	200	1181	2400	200	1181	2400	200	1181	2400	200								
S-LOC 32L	1440	2400	459	1440	2400	459	1440	4500	459	1440	4500	459								
CIRCLING	1660	1	675	1680	1	695	2000	3	1015	2040	3	1055								
NOTES: CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON OVR VORTAC AIRWAY RADIALS 245 CW 332. EQUIPMENT REQUIREMENTS NOTE: DME REQUIRED FOR LOC ONLY.														@ CAT C, D 1100-3						
CITY AND STATE OMAHA, NE				ELEVATION: 985 TDZE: 981 AIRPORT NAME: EPPLEY AIRFIELD			FACILITY IDENTIFIER: I-ENF		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 32L, AMDT 3 24 MAY 2018					SUP: AMDT: 2A DATED 03/05/2015						



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**ILS - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY  
23  
CHECKED

CITY AND STATE

OMAHA, NE

ELEVATION: 985

TDZE: 981

AIRPORT NAME:

EPPLEY AIRFIELD

FACILITY  
IDENTIFIER:  
**I-ENF**

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
**ILS OR LOC RWY 32L, AMDT 3**  
24 MAY 2018

SUP:

AMDT: **2A**

DATED: **03/05/2015**