

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW32R CLIMB TO 1800 THEN CLIMBING LEFT TURN TO 3300 DIRECT OTSEE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 142.30 INBOUND. CHART FAS OBST: 1415 TOWER 411515N/0955008W. CHART 1287 TREE 411650N/0955123W. DISTANCE TO THLD FROM 200 HAT: 0.45 NM. CHART VDP AT 2.01 NM TO RW32R* *LNAV ONLY. WAAS CHANNEL # 90599 REFERENCE PATH ID: W32B CHART CIRCLING ICON. LTP HAE: 271.4 M											
MEPWE	CUTBO (TF) (FO) (RNP 2.00)	081.17 / 16.52	4000												
OVR VORTAC	CUTBO (TF) (FO) (RNP 2.00)	159.78 / 3.09	4000												
EMEND (IAF)	CUTBO (NOPT) (TF) (FB) (RNP 1.00)	280.28 / 13.09	4000												
VIKKI (IAF)	CUTBO (NOPT) (TF) (FB) (RNP 1.00)	329.80 / 28.95	4000												
CUTBO (IF/IAF) (SEE FORM 8260-10)	BEEFF (TF) (FB) (RNP 1.00)	322.51 / 7.46	2800												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE CUTBO, RT, 322.51 INBOUND, 4000 FT. IN LIEU OF PT (IAF) 3. FAC: 322.45 FAF: BEEFF _____ DIST FAF TO MAP: 5.54 THLD: 5.54 4. MIN. ALT: CUTBO 4000, BEEFF 2800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2800 GS ALT AT: BEEFF 2800 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 55.0 34:1 IS CLEAR 8. MSA FROM: RW32R 3900				MAG VAR: 2E EPOCH YEAR: 2020											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		STANDARD @									
CATEGORY >>>>>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1181	1800	200	1181	1800	200	1181	1800	200	1181	1800	200			
LNAV/VNAV DA	1611	1 3/8	630	1611	1 3/8	630	1611	1 3/8	630	1611	1 3/8	630			
LNAV MDA	1680	2400	699	1680	2400	699	1680	1 1/2	699	1680	1 1/2	699			
CIRCLING	1680	1	695	1680	1	695	2000	3	1015	2040	3	1055			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-2F) OR ABOVE 37C (99F). @ CAT C, D 1100-3 CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON OVR VORTAC AIRWAY RADIALS 072 CW 245. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/4 SM.															
CITY AND STATE OMAHA, NE		ELEVATION: 985 TDZE: 981 AIRPORT NAME: EPPLEY AIRFIELD		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 32R, AMDT 1 24 MAY 2018				SUP: AMDT: ORIG-B DATED 09/20/2012					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
BEEFF (FAF)	RW32R (MAP) (TF) (FO) (RNP 0.30)	322.45 / 5.54	
RW32R (MAP)	1800 MSL (CA)	322.45	1800
1800 MSL	OTSEE (DF) (FO) (RNP 1.00)		3300

QUALITY
18
CHECKED

CITY AND STATE
OMAHA, NE

ELEVATION: 985 **TDZE: 981**
 AIRPORT NAME:
 EPPLEY AIRFIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Y RWY 32R, AMDT 1
 24 MAY 2018

SUP:
 AMDT: **ORIG-B**
 DATED: **09/20/2012**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KOMA
RUNWAY	RW32R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W32B
LTP/FTP LATITUDE	411740.4315N
LTP/FTP LONGITUDE	0955256.6630W
LTP/FTP ELLIPSOIDAL HEIGHT	+02714
FPAP LATITUDE	411852.9125N
FPAP LONGITUDE	0955405.4940W
THRESHOLD CROSSING HEIGHT (TCH)	00055.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0160
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 4066D521

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02991
FPAP ORTHOMETRIC HEIGHT	+02991

QUALITY
18
CHECKED

CITY AND STATE OMAHA, NE	ELEVATION: 985 AIRPORT NAME: EPPLEY AIRFIELD	TDZE: 981 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 32R, AMDT 1 24 MAY 2018	SUP:
				AMDT: ORIG-B
				DATED: 09/20/2012