

RNAV - STANDARD US DEPARTMENT OF TRANSPORTATION INSTRUMENT APPROACH PROCEDURE FEDERAL AVIATION ADMINISTRATION TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH									
FROM	TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 3000 DIRECT CIVIL AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 358.21 INBOUND. CHART FAS OBST: 1319 TREE 412031N/0955245W. 1444 AAO 412433N/0955215W. DISTANCE TO THLD FROM 200 HAT: 0.46 NM. CHART VDP AT 1.52 NM TO RW18* *LNAV ONLY. WAAS CHANNEL # 65617 REFERENCE PATH ID: W18A CHART CIRCLING ICON. LTP HAE: 271.3 M										
OVR VORTAC	TASKY (TF) (FO) (RNP 2.00)			338.77 / 21.45			3000												
KENAR	TASKY (TF) (FO) (RNP 2.00)			079.90 / 19.84			3000												
GLENE	TASKY (TF) (FO) (RNP 2.00)			278.48 / 17.82			2900												
CANIO (IAF)	TASKY (NOPT) (TF) (FB) (RNP 1.00)			155.17 / 9.23			3000												
TASKY (IF/IAF)	CEPUT (TF) (FB) (RNP 1.00)			178.21 / 5.95			2800												
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD N TASKY, RT, 178.21 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 178.21 FAF: CEPUT DIST FAF TO MAP: 5.55 THLD: 5.55 4. MIN. ALT: TASKY 3000, CEPUT 2800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2800 GS ALT AT: CEPUT 2800 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 51.8 34:1 IS CLEAR 8. MSA FROM: RW18 3900																MAG VAR: 2E		EPOCH YEAR: 2020	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @										
CATEGORY >>>>>	A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA **	1182	2400	200	1182	2400	200	1182	2400	200	1182	2400	200							
LNAV/VNAV DA	1540	6000	558	1540	6000	558	1540	6000	558	1540	6000	558							
LNAV MDA	1520	2400	538	1520	2400	538	1520	5500	538	1520	5500	538							
CIRCLING	1660	1	675	1680	1	695	2000	3	1015	2040	3	1055							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C (-4F) OR ABOVE 54C (130F). @ CAT C, D 1100-3 CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON OVR VORTAC AIRWAY RADIALS 245 CW 072. CHART NOTE: ** RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.																			
CITY AND STATE			ELEVATION: 985 TDZE: 982			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:						
OMAHA, NE			AIRPORT NAME:			RNAV			RNAV (GPS) Y RWY 18, AMDT 4				AMDT: 3A						
			EPPLEY AIRFIELD						24 MAY 2018				DATED 10/12/2017						



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
CEPUT (FAF)	RW18 (MAP) (TF) (FO) (RNP 0.30)	178.21 / 5.55	
RW18 (MAP)	1182 MSL (CA)	178.21	
1182 MSL	CIVIV (DF) (FO) (RNP 1.00)		3000

QUALITY
18
CHECKED

CITY AND STATE
OMAHA, NE

ELEVATION: 985 TDZE: 982
AIRPORT NAME:
EPPLEY AIRFIELD

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Y RWY 18, AMDT 4
24 MAY 2018

SUP:
AMDT: 3A
DATED: 10/12/2017

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KOMA
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	411846.6750N
LTP/FTP LONGITUDE	0955340.2410W
LTP/FTP ELLIPSOIDAL HEIGHT	+02713
FPAP LATITUDE	411717.5275N
FPAP LONGITUDE	0955340.6745W
THRESHOLD CROSSING HEIGHT (TCH)	00051.8
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0312
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 8899F243

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+02991
FPAP ORTHOMETRIC HEIGHT	+02991

QUALITY
18
CHECKED

CITY AND STATE OMAHA, NE	ELEVATION: 985 AIRPORT NAME: EPPLEY AIRFIELD	TDZE: 982 	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 18, AMDT 4 24 MAY 2018	SUP:
					AMDT: 3A
					DATED: 10/12/2017