

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW01
MIOLA	EPFOW (FB)	215.59 / 5.51	2000	CLIMBING RIGHT TURN TO 3000 DIRECT MIOLA AND HOLD.
EPFOW (IAF)	ZOMTO (FB)	271.53 / 7.66	1900	
ZOMTO (IF)	GIXGO (FB)	007.02 / 6.10	1500	
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 183.75 INBOUND. CHART FAS OBST: 542 TOWER 353126N/0893455W GIXGO TO RW01: 3.03/40

1. PT NA SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)
 2. PROFILE STARTS AT ZOMTO
 3. FAC: 007.03 FAF: GIXGO DIST FAF TO MAP: 3.67 THLD: 3.67
 4. MIN. ALT: ZOMTO 1900, GIXGO 1500
 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____
 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____
 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR
 8. MSA FROM: RW01 2500

MAG VAR: 2E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N/A					STANDARD @						
CATEGORY =====>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA		800	1	520	800	1	520	800	1 1/2	520	800	1 3/4	520			
CIRCLING		800	1	520	800	1	520	800	1 1/2	520	840	2	560			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MEMPHIS ALTIMETER SETTING AND INCREASE
 SEE 8260-10

CITY AND STATE COVINGTON, TN	ELEVATION: 280 TDZE: 280 AIRPORT NAME: COVINGTON MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 22 OCT 2009	SUP:
				AMDT: NONE
				DATED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

ALL MDA 100 FEET AND INCREASE LNAV CATS C/D AND CIRCLING CAT C VISIBILITIES 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA AT MIOLA ON V11 NORTHBOUND AND V124 EASTBOUND.

CITY AND STATE

COVINGTON, TN

ELEVATION: 280

TDZE: 280

AIRPORT NAME:

COVINGTON MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, ORIG

22 OCT 2009

SUP:

AMDT: **NONE**

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	MIOLA	MIOLA	010		IF		FB				
	MIOLA	EPFOW	020	IAF	TF		FB	2.0	215.6 (218T)	005.5	02000
	MIOLA	ZOMTO	030		TF		FB	1.0	271.5 (274T)	007.7	01900
		ZOMTO	010	FACF	IF		FB				01900
		GIXGO	020	PAF	TF		FB	0.5	007.0 (009T)	006.1	01500
		RW01	030	MAP	TF		FO	0.3	007.0 (009T)	003.7	00320

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	MIOLA	040		DF	R	FO	1.0			03000
	MIOLA	050		HM	R	FO	2.0	183.8 (186T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	EPFOW	N352427.87	W0892749.99	N3524.465	W08927.833
	GIXGO	N353057.96	W0893601.14	N3530.966	W08936.019
	MIOLA	N352850.14	W0892343.44	N3528.836	W08923.724
	ZOMTO	N352455.86	W0893711.46	N3524.931	W08937.191
	RW01	N353435.68	W0893518.77	N3534.595	W08935.313

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW01	00280	40

QUALITY
CHECKED

CITY AND STATE
COVINGTON, TN

ELEVATION: 280 TDZE: 280
 AIRPORT NAME:
 COVINGTON MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
 RNAV (GPS) RWY 1, ORIG
 22 OCT 2009

SUP:
 AMDT: NONE
 DATED: