

**Federal Aviation
Administration**

Transmittal Letter 16-17

July 1, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
18-Aug-16	PA	St Marys	St Marys Muni	6/1829	6/22/16	RNAV (GPS) RWY 28, Amdt 1B

AIRAC Date: 18 AUGUST 2016

FDC 6/1829 OYM IAP ST MARYS MUNI, ST MARYS, PA. RNAV (GPS) RWY 28, AMDT 1B...
LPV DA 2208/HAT 274 ALL CATS. LNAV CAT C/D VIS 1 3/4. DELETE NOTE: PROCEDURE
NA AT NIGHT. CHANGE INOPERATIVE TABLE DOES NOT APPLY NOTE TO READ:
INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS AND LNAV CAT A/B. CHART
NOTE: FOR INOPERATIVE MALS, INCREASE LNAV CAT D VISIBILITY TO 2 MILE. DELETE
NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. 34:1 IS
CLEAR. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE BRADFORD ALTIMETER SETTING AND INCREASE ALL
DA/MDA 240 FT, AND LPV ALL CATS VISIBILITY 5/8 MILE, LNAV CAT C/D 3/4 MILE, AND
CIRCLING CAT A/D 1/4 MILE AND CAT B 1/2 MILE AND CAT C 1 MILE. CHART NOTE:
WHEN USING BRADFORD ALTIMETER SETTING, INOPERATIVE TABLE DOES NOT APPLY
TO LNAV CAT C/D. CHART NOTE: FOR INOPERATIVE MALS WHEN USING BRADFORD
ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 7/8 MILE. CHART VDP AT
2.08 MILES TO RW28* *LNAV ONLY. CHART NOTE: VDP NA WHEN USING BRADFORD
ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 28, AMDT 1C. 1603041310-PER