

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES							MISSED APPROACH								
FROM		TO		COURSE AND DISTANCE		ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW18 CLIMB TO 3000 DIRECT USUDY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 001.68 INBOUND. CHART FAS OBST: 346 TREE 350917N/0904850W. CHART 657 TOWER 351047N/0904916W DISTANCE TO THLD FROM 321 HATH: 0.88 NM. WAAS CHANNEL # 65832 REFERENCE PATH ID: W18A CHART CIRCLING ICON CHART WEST MEMPHIS ASOS LTP HAE: 45.8 M								
UHIHI (IF/IAF)		YAGUK (FB)		181.69 / 6.20		2100									
YAGUK (FAF)		WUGAB/2.80 NM TO RW18 (FB)		181.69 / 2.92											
WUGAB/2.80 NM TO RW18		RW18 (MAP) (FO)		181.69 / 2.80											
RW18 (MAP)		560 MSL		181.69											
560 MSL		USUDY (FO)				3000									
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD N UHIHI, RT, 181.69 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>181.69</u> FAF: <u>YAGUK</u> DIST FAF TO MAP: <u>5.72</u> THLD: <u>5.72</u> 4. MIN. ALT: <u>UHIHI 3000, YAGUK 2100, WUGAB/2.80 NM TO RW18 1160*</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCLPT: <u>2100</u> GS ALT AT: <u>YAGUK 2100</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS CLEAR 8. MSA FROM: <u> </u>							MAG VAR: 1W EPOCH YEAR: 2015								
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A <input checked="" type="checkbox"/> X								
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	560	1 1/8	321	560	1 1/8	321		NA			NA				
LNAV/VNAV DA	560	1 1/8	321	560	1 1/8	321		NA			NA				
LNAV MDA	680	1	441	680	1	441		NA			NA				
CIRCLING	840	1	601	840	1	601		NA			NA				
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: USE WEST MEMPHIS ALTIMETER SETTING; WHEN NOT RECEIVED, USE TUNICA ALTIMETER SETTING AND INCREASE ALL DA/MDA 20 FT. CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY															
CITY AND STATE			ELEVATION: 239 THRE: 239			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:			
COLT, AR			AIRPORT NAME:			RNAV			RNAV (GPS) RWY 18, ORIG			AMDT: NONE			
			DELTA REGIONAL AIRPORT						29 MAY 2014			DATED			

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	092/30 CW 272/30 (NOPT)	UHIHI (IF/IAF) (FB)	3000
2.	272/30 CW 092/30	UHIHI (IF/IAF) (FO)	3000

CITY AND STATE

COLT, AR

ELEVATION: 239

THRE: 239

AIRPORT NAME:

DELTA REGIONAL AIRPORT

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

29 MAY 2014

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KDRP
RUNWAY	RW18
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W18A
LTP/FTP LATITUDE	350736.9430N
LTP/FTP LONGITUDE	0904935.0405W
LTP/FTP ELLIPSOIDAL HEIGHT	+00458
FPAP LATITUDE	350607.7000N
FPAP LONGITUDE	0904936.3500W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

E9E8330D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00728
FPAP ORTHOMETRIC HEIGHT	+00728

CITY AND STATE

COLT, AR

ELEVATION: 239

THRE: 239

AIRPORT NAME:

DELTA REGIONAL AIRPORT

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 18, ORIG

29 MAY 2014

SUP:

AMDT:

NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KDRPK4FR18	AUHIHI	010UHIHIK4EA0EE	AR	HF		18170040		+ 03000	18000			A JS	
SUSAP KDRPK4FR18	R	010UHIHIK4EA0E	I	IF				+ 03000	18000			A JS	
SUSAP KDRPK4FR18	R	020YAGUKK4EA1E	F	051TF		18170062		+ 02100				A JS	
SUSAP KDRPK4FR18	R	020YAGUKK4EA2WALPV			ALNAV/VNAV ALNAV							JS	
SUSAP KDRPK4FR18	R	021WUGABK4EA0E	S	031TF		18170029		V 0116001171		-300		A JS	
SUSAP KDRPK4FR18	R	030RW18 K4PGOGY	M	031TF		18170028		00279		-300		A JS	
SUSAP KDRPK4FR18	R	040		0 M	CA	1817		+ 00560				A JS	
SUSAP KDRPK4FR18	R	050USUDYK4EA0EY		DF				+ 03000				A JS	
SUSAP KDRPK4FR18	R	060USUDYK4EA0EE	R	HM		00170040		+ 03000				A JS	

[illegible][illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	UHIHI	UHIHI	010	IAF	HF	R	FO		181.7(180.7T)	004.0	AA 03000	
		UHIHI	010	FACF	IF		FB				AA 03000	
		YAGUK	020	FAP	TF		FB	0.5	181.7(180.7T)	006.2	AA 02100	
		WUGAB	021	SDF	TF		FB	0.3	181.7(180.7T)	002.9	AA 01160	GS 01171
		RW18	030	MAP	TF		FO	0.3	181.7(180.7T)	002.8	AT 00279	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		181.7(180.7T)		AA 00560	
	USUDY	050		DF		FO				AA 03000	
	USUDY	060		HM	R	FO		001.7(000.7T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	UHIHI	N351933.12	W0904924.53	N3519.552	W09049.409
	USUDY	N345449.37	W0904946.11	N3454.823	W09049.769
	WUGAB	N351025.20	W0904932.57	N3510.420	W09049.543
	YAGUK	N351320.56	W0904930.00	N3513.343	W09049.500
	RW18	N350736.94	W0904935.04	N3507.616	W09049.584

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW18	00239	40

CITY AND STATE COLT, AR	ELEVATION: 239 THRE: 239	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG 29 MAY 2014	SUP:
	AIRPORT NAME: DELTA REGIONAL AIRPORT			AMDT: NONE
				DATED: