

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: ELEDE CLIMB TO 8200 DIRECT OWEVU AND ON TRACK 035.09 TO RLY VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 159.00 INBOUND. CHART FAS OBST: 5007 TREE 434246N/1082448W 6811 AAO 433927N/1083503W 5702 AAO 434039N/1083009W CHART CIRCLING ICON. WIBTI TO RW05: 3.54/50. FINAL APPROACH COURSE OFFSET 19.74 DEGREES. FAC CROSSES RWY C/L EXTENDED 4506 FT FROM THLD.					
RLY VOR/DME		DIMSE (TF) (FB) (RNP 2.00)		266.46 / 28.57				8200							
DIMSE (IAF)		CASPI (NOPT) (TF) (FB) (RNP 1.00)		183.93 / 19.58				8000							
CASPI (IF)		WIBTI (TF) (FB) (RNP 1.00)		094.97 / 6.02				8000							
WIBTI (FAF)		SHOTE/3.80 NM TO ELEDE (TF) (FB) (RNP 0.30)		066.48 / 3.69											
SHOTE/3.80 NM TO ELEDE		KARST/1.80 NM TO ELEDE (TF) (FB) (RNP 0.30)		066.48 / 2.00											
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT CASPI 3. FAC: 066.48 FAF: WIBTI DIST FAF TO MAP: 7.49 THLD: 8.19 4. MIN. ALT: CASPI 8000, WIBTI 8000, SHOTE/3.80 NM TO ELEDE 6620, KARST/1.80 NM TO ELEDE 5860 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR 8. MSA FROM: ELEDE 12000															
										MAG VAR: 10E			EPOCH YEAR: 2020		
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @			
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	5240	1	358	5240	1	358	5240	1	358		NA				
CIRCLING	5320	1	428	5540	1	648	5580	2	688	5880	3	988			
NOTES: CHART NOTE: CIRCLING NA NW OF RWY 05-23. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: RWY 5 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON RLY VOR/DME ON AIRWAY RADIALS 194 CW 299.															
CITY AND STATE		ELEVATION: 4892 TDZE: 4882		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
THERMOPOLIS, WY		AIRPORT NAME:				RNAV (GPS) RWY 5, ORIG				AMDT: NONE					
		HOT SPRINGS COUNTY				2 MARCH 2017				DATED					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
KARST/1.80 NM TO ELEDE	ELEDE (MAP) (TF) (FO) (RNP 0.30)	066.48 / 1.80	
ELEDE (MAP)	5240 MSL	066.61	
5240 MSL	OWEVU (DF) (FB) (RNP 1.00)		
OWEVU	RLY VOR/DME (TF) (FO) (RNP 1.00)	035.09 / 20.42	8200

CITY AND STATE
THERMOPOLIS, WY

ELEVATION: 4892 TDZE: 4882
AIRPORT NAME:
HOT SPRINGS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 5, ORIG
2 MARCH 2017

SUP:
AMDT: NONE
DATED:

QUALITY
18
CHECKED