

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		RNP: DA CLIMB TO 3400 DIRECT EGYAZ AND ON TRACK 173.33 TO LAKVE AND ON TRACK 122.12 TO MRIAM AND ON TRACK 079.23 TO ADRYN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 260.00 INBOUND. DISTANCE TO THLD FROM 392 HAT: 1.04 NM. ROUTE TYPE QUALIFIER 2: S ROUTE TYPE QUALIFIER 1: F ROUTE TYPE: A, H #TCH 991.39 MSL (DO NOT CHART) CHART MANDATORY 8000 AT RAFII. CHART MANDATORY 9000 AT EAGLZ.					
RAFII (IAF)		AYKAY (TF) (FB) (RNP 1.00)		151.36 / 2.17				7300							
AYKAY		SAKOH (TF) (FB) (RNP 0.70)		151.37 / 1.63				6800							
SAKOH		TAKOE (TF) (FB) (RNP 0.70)		188.22 / 7.88				4300							
EAGLZ (IAF)		RUXNN (TF) (FB) (RNP 0.70)		189.23 / 4.00				7800							
RUXNN		GAREY (TF) (FB) (RNP 0.70)		189.22 / 2.59				7200							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)															
2. PROFILE STARTS AT TAKOE															
3. FAC: <u>258.05</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____															
4. MIN. ALT: TAKOE 4300, SCRIM 2900															
5. DIST TO THLD FROM OM: <u>5.99</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: <u>2900</u> GS ALT AT: SCRIM 2900 OM: _____ MM: _____ IM: _____															
7. GS ANGLE: <u>3.00</u> TCH: <u>59.7</u> # <u>34:1</u> IS CLEAR															
8. MSA FROM: RW26R 11300										MAG VAR: 12E			EPOCH YEAR: 2020		
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
AUTHORIZATION REQUIRED															
RNP 0.30 DA	1324	4000	392	1324	4000	392	1324	4000	392	1324	4000	392			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW 1C (34F) OR ABOVE 54C (130F). CHART NOTE: GPS REQUIRED. CHART PLANVIEW NOTE AT AYKAY: (RNP 0.50). CHART PLANVIEW NOTE AT EAGLZ: (RNP 0.50). (CONTINUED ON PAGE 2)															
CITY AND STATE		ELEVATION: 944 TDZE: 932				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:			
ONTARIO, CA		AIRPORT NAME:						RNAV (RNP) Z RWY 26R, AMDT 1				AMDT: ORIG-D			
		ONTARIO INTL						27 APRIL 2017				DATED 05/26/2016			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33					
TERMINAL ROUTES, (CONT.):					
FROM		TO	COURSE AND DISTANCE	ALTITUDE	
GAREY		ZIGGY (TF) (FB) (RNP 0.70)	213.07 / 3.94	6000	
ZIGGY		TAKOE (TF) (FB) (RNP 0.70)	213.08 / 5.37	4300	
TAKOE (IF)		SCRIM (TF) (FB) (RNP 0.50)	258.31 / 4.87	2900	
SCRIM (FAF)		RW26R (MAP) (TF) (FO)	258.05 / 5.99		
RW26R (MAP)		1324 MSL	258.05		
1324 MSL		EGYAZ (DF) (FB) (RNP 1.00)			
EGYAZ		LAKVE (TF) (FB) (RNP 1.00)	173.33 / 5.25		
LAKVE		MRIAM (TF) (FB) (RNP 1.00)	122.12 / 4.25		
MRIAM		ADRYN (TF) (FO) (RNP 1.00)	079.23 / 3.11	3400	
NOTES, (CONT.):					
CHART PROFILE NOTE: VGSi AND RNAV GLIDEPATH NOT COINCIDENT (VGSi ANGLE {ANGLE}/TCH {FEET}).					
CHART SPEED ICON IN PLANVIEW AT RAFII, EAGLZ : MAX 240 KIAS.					
CHART SPEED ICON IN PLANVIEW AT TAKOE : MAX 210 KIAS.					
<div>QUALITY 20 CHECKED</div>					
CITY AND STATE		ELEVATION: 944	TDZE: 932	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	
ONTARIO, CA		AIRPORT NAME:	FACILITY IDENTIFIER:	RNAV (RNP) Z RWY 26R, AMDT 1	
		ONTARIO INTL	RNAV	27 APRIL 2017	
				SUP:	
				AMDT: ORIG-D	
				DATED: 05/26/2016	