

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: GRO NDB								
ERTTS INT/UNZ 46.00 DME			GRO NDB			087.09 / 12.29			3100		CLIMBING RIGHT TURN TO 2000 ON HEADING 360 THEN CONTINUE CLIMBING RIGHT TURN TO 3100 DIRECT GRO NDB AND HOLD.								
KAQTU/UNZ 23.00 DME			GRO NDB			030.74 / 29.09			3100										
										ADDITIONAL FLIGHT DATA: HOLD E, RT, 260.00 INBOUND. CHART FAS OBST: 661 TREE 141022N/1451457E CHART 3100 PRIOR TO GRO NDB IN PROFILE. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 1788 FT FROM THLD.									
1. PT <u>L</u> SIDE OF COURSE <u>080.00</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>GRO NDB</u> (IAF)																			
2.																			
3. FAC <u>260.00</u> FAF										DIST FAF TO MAP THLD									
4. MIN. ALT																			
8. MSA FROM: <u>GRO NDB 2900</u>										MAG VAR: <u>2E</u> EPOCH YEAR: <u>1985</u>									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: <u>N A</u>		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-27		1120	1	513	1120	1	513	1120	1 3/8	513	1120	1 3/8	513						
CIRCLING		1120	1	513	1120	1	513	1120	1 1/2	513	1160	2	553						
NOTES:																			
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ANDERSEN AFB ALTIMETER SETTING AND INCREASE ALL MDA 320 FT, INCREASE S-27 CAT B VISIBILITY 1/4 MILE, CAT C, D VISIBILITY 1 1/8 MILE, CIRCLING CAT A, B VISIBILITY 1/4 MILE, CAT C 1 MILE, CAT D 3/4 MILE.										@ NA EXCEPT STANDARD FOR OPERATORS WITH APPROVED WEATHER REPORTING SERVICE.									
CHART NOTE: CIRCLING NA S OF RWY 09-27.																			
CITY AND STATE		ELEVATION: 607 TDZE: 607			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			QUALITY				
ROTA ISLAND, CQ		AIRPORT NAME:			GRO			NDB RWY 27, AMDT 4A				AMDT			4				
		BENJAMIN TAISACAN MANGLONA INTL						2 MARCH 2017				DATE			02/06/2014				