

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
<b>TERMINAL ROUTES</b>											<b>MISSED APPROACH</b>				
FROM		TO			COURSE AND DISTANCE				ALTITUDE		RNP: DA  (DO NOT EXCEED 230 KIAS UNTIL WRENS) CLIMB TO 2300 ON THE RNAV MISSED APPROACH ROUTE TO WRENS AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD E, RT, 263.27 INBOUND. DISTANCE TO THLD FROM 250 HAT: 0.63 NM. ROUTE TYPE: A, H ROUTE TYPE QUALIFIER1: F ROUTE TYPE QUALIFIER2: S #TCH 58.8 (DO NOT CHART)				
HAVNU (40E) WRENS (IAF) (40E) (43A) TEGUA CCW (IF)(40E)(42R)(43B) NAIRA (40E) (43I)		WRENS (TF) (FB) RNP 1.00 (40E) (43A) TEGUA (TF) (FB) RNP 1.00 (40E) (43B) NAIRA (RF) (FB) RNP 0.30 (40E) (42R) VIZOR (TF) (FB) RNP 0.30 (40E) (43F)			268.91 / 25.33 263.27 / 12.07 (4.00 NM RADIUS CCW CFCLH)/12.57 83.25 / 2.00				7000 2300 2300 1900		2300 1900          2300				
BIRUQ (IAF) (40E) (43A) NAIRA (IF) (40E) (43I) VIZOR (FAF) (40E) (43F) RW09: (MAP) (40G) (43M) RIPIE (40E) SAKAE (40E) ZULTO CCW (40E) (42R) YOGAS CCW (40E) (42R)		NAIRA (TF) (FB) RNP 0.50 (40E) (43B) VIZOR (TF) (FB) RNP 0.30 (40E) (43F) RW09 (TF) (FB) (40G) (43M) RIPIE (TF) (FB) RNP 0.15 (40E) (42M) SAKAE (TF) (FB) RNP 0.20 (40E) ZULTO (TF) (FB) RNP 0.30 (40E) (42R) YOGAS (RF) (FB) RNP 0.50 (40E) (42R) WRENS (RF) (FO) RNP 1.00 (40E) (41Y)			88.77 / 22.15 83.25 / 2.00 83.25 / 5.78 83.25 / 1.70 83.25 / 1.26 83.25 / 1.33 (4.00 NM RADIUS CCW CFCMK)/4.21 (4.00 NM RADIUS CCW CFCMK)/8.36										
1. PT <u>NA</u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF) 2. PROFILE STARTS AT VIZOR 3. FAC: <u>83.25</u> FAF: <u>      </u> DIST FAF TO MAP: <u>      </u> THLD: <u>      </u> 4. MIN ALT: <u>VIZOR 1900</u> 5. DIST TO THLD FROM OM: <u>5.78</u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u> 6. MIN GS INCPT: <u>1900</u> GS ALT AT: <u>VIZOR 1900</u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>50.0</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW09 3800</u>											MAG VAR: 7E EPOCH YEAR: 1985				
<b>MINIMUMS</b>															
TAKEOFF: SEE FORM 8260-15 FOR THIS AIRPORT						ALTERNATE: N A				STANDARD					
<b>CATEGORY ==&gt;</b>	<b>A</b>			<b>B</b>			<b>C</b>			<b>D</b>			<b>E</b>		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
<b>AUTHORIZATION REQUIRED</b>															
RNP 0.15 DA	259	1	250	259	1	250	259	1	250	259	1	250			
NOTES:															
CHART NOTE: OBTAIN LOCAL ALTIMETER SETTING ON CTAF; WHEN NOT RECEIVED, PROCEDURE NA.															
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW 20C (68F) OR ABOVE 54C (130F).															
CHART NOTE: MISSED APPROACH REQUIRES RNP LESS THAN 1.0.															
CHART NOTE: RF REQUIRED.															
CHART NOTE: GPS REQUIRED.															
CHART NOTE: NO CONTROLLED AIRSPACE BELOW 5500 FEET.															
CITY AND STATE		ELEVATION: 9 TDZE: 9		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:						SUP:			
POHNPEI ISLAND, FM		AIRPORT NAME:		RNAV		RNAV (RNP) Z RWY 9, AMDT 1 26 MAY 2016						AMDT: NONE			
		POHNPEI INTL										DATED:			

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>RNAV                      INSTRUMENT APPROACH PROCEDURE</b> FLIGHT STANDARDS SERVICES <b>97.33</b>			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
NOTES CONT: CHART SPEED ICON IN PLANVIEW AT TEGUA: MAX 230 KIAS. CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.				
CITY AND STATE  POHNPEI ISLAND, FM	ELEVATION: 9                      TDZE: 9 AIRPORT NAME: POHNPEI INTL	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:  RNAV (RNP) Z RWY 9, AMDT 1 26 MAY 2016	SUP: AMDT: NONE DATED: