

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**VOR STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICE - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
				7.65 MILES AFTER IOW VORTAC OR AT NUYIB/IOW 7.65 DME FIX
				CLIMBING LEFT TURN TO 2600 DIRECT IOW VORTAC AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD S, LT, 017.00 INBOUND. CHART FAS OBST: 889 TOWER 413723N/0913414W CHART: 895 TOWER 413940N/0913251W FAC CROSSES MID POINT OF RWY 12-30.

1. PT R SIDE OF COURSE 197.29 OUTBOUND 2300 FT WITHIN 10 MILES OF IOW VORTAC (IAF)
2. \_\_\_\_\_
3. FAC 017.29 FAF IOW VORTAC DIST FAF TO MAP 7.65 THLD \_\_\_\_\_
4. MIN. ALT IOW VORTAC 2300
8. MSA FROM: IOW VORTAC 3300

MAG VAR: 5E EPOCH YEAR: 1965

MINIMUMS															
TAKEOFF:	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A			STANDARD @					
CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
CIRCLING	1280	1	612	1280	1	612		NA			NA				

NOTES:

CHART NOTE: IF LOCAL ALTIMETER SETTING NOT RECEIVED, USE CEDAR RAPIDS ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET.

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE <b>IOWA CITY, IA</b>	ELEVATION: 668 TDZE: AIRPORT NAME: <b>IOWA CITY MUNI</b>	FACILITY IDENTIFIER: <b>IOW</b>	PROCEDURE NO./ AMDT NO./ EFFECTIVE DATE: <b>VOR-A, ORIG</b> <b>JAN 18 2007</b>	SUP AMDT <b>NONE</b> DATE
--	--	------------------------------------	--	---------------------------------

