

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION TACAN OR VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 6.56 MILES AFTER SWL VORTAC OR AT SWL 6.56 DME FIX CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 2000 DIRECT SWL VORTAC AND HOLD (TACAN AIRCRAFT CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 2000 ON HEADING 300 AND SWL VORTAC R-219 TO WAFIT/SWL 5.00 DME AND HOLD SW, LT, 039.00 INBOUND). ADDITIONAL FLIGHT DATA: HOLD SW, LT, 039.05 INBOUND. FAS OBST: 249 AAO 380146N/0752842W CHART R-6604. SWL VORTAC TO RW17: 2.76/45. CHART CIRCLING ICON.							
1. PT <u>R</u> SIDE OF COURSE <u>009.67</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>SWL VORTAC</u> (IAF) 2. _____ 3. FAC <u>189.67</u> FAF <u>SWL VORTAC</u> DIST FAF TO MAP <u>6.56</u> THLD <u>6.56</u> 4. MIN. ALT <u>SWL VORTAC 2000</u> 8. MSA FROM: <u>SWL VORTAC 045-315 1600, 315-045 2100</u>														MAG VAR: 8W		EPOCH YEAR: 1965	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @							
CATEGORY ==>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-17	540	1	509	540	1	509	540	1 3/8	509	540	1 3/8	509					
CIRCLING	600	1	560	600	1	560	620	1 1/2	580	860	2 3/4	820					
NOTES: CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN RWY 10 VGSI INOPERATIVE, CIRCLING TO RWY 10-NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SALISBURY ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND S-17 CATS C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE. (SEE FORM 8260-10)																	
CITY AND STATE				ELEVATION: 40 THRE: 31				FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP			
WALLOPS ISLAND, VA				AIRPORT NAME:				SWL		VOR OR TACAN RWY 17, AMDT 7 19 SEPTEMBER 2013				AMDT 6B			
				WALLOPS FLIGHT FACILITY										DATE 07/10/2003			

QUALITY
2
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
TACAN OR VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON SWL VORTAC AIRWAY RADIALS 360 CW 034.

QUALITY
2
CHECKED

CITY AND STATE WALLOPS ISLAND, VA	ELEVATION: 40	THRE: 31	FACILITY IDENTIFIER: SWL	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: VOR OR TACAN RWY 17, AMDT 7 19 SEPTEMBER 2013	SUP:
	AIRPORT NAME: WALLOPS FLIGHT FACILITY	AMDT: 6B			
	DATED: 07/10/2003				