

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW22					
ABI VORTAC		ZANGU (TF) (FB) (RNP 2.00)		057.88 / 17.07				4000		CLIMBING RIGHT TURN TO 4000 DIRECT ULOYO AND HOLD.					
FLECK		VAYUS (TF) (FB) (RNP 2.00)		031.72 / 7.29				4000							
ROGEE (IAF)		ULLOYO (NOPT) (TF) (FB) (RNP 1.00)		213.58 / 19.14				4000		ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1913 DERRICK 322620N/0993904W CHART: ASR. CHART: ELMDALE AIRPARK (PVT) ON PLANVIEW. CHART VDP AT 1.16 NM TO RW22. CHART CIRCLING ICON. JOKPI TO RW22: 3.05/40.					
ZANGU (IAF)		ULLOYO (NOPT) (TF) (FB) (RNP 1.00)		137.35 / 5.00				4000							
VAYUS (IAF)		ULLOYO (NOPT) (TF) (FB) (RNP 1.00)		317.41 / 5.00				4000							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)															
2. HOLD NE ULOYO, RT, 227.38 INBOUND, 4000 FT. IN LIEU OF PT (IAF)															
3. FAC: 227.33 FAF: JOKPI DIST FAF TO MAP: 5.56 THLD: 5.56															
4. MIN. ALT: ULOYO 4000, JOKPI 3600, YARUG/2.80 NM TO RW22 2700															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 34:1 IS CLEAR															
8. MSA FROM: RW22 4600															
MAG VAR: 5E EPOCH YEAR: 2020															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD			
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2180	1	416	2180	1	416	2180	1 1/8	416	2180	1 1/8	416			
CIRCLING	2300	1	509	2320	1	529	2420	1 3/4	629	2460	2	669			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON ABI VORTAC AIRWAY RADIALS 037 CW 099.															
CITY AND STATE ABILENE, TX		ELEVATION: 1791 TDZE: 1764 AIRPORT NAME: ABILENE RGNL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG-A, 01/05/2017						SUP: AMDT: ORIG DATED 01/15/2009			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
ULOYO (IF/IAF)	JOKPI (TF) (FB) (RNP 1.00)	227.38 / 6.10	3600
JOKPI (FAF)	YARUG/2.80 NM TO RW22 (TF) (FB) (RNP 0.30)	227.33 / 2.76	
YARUG/2.80 NM TO RW22	RW22 (MAP) (TF) (FO) (RNP 0.30)	237.33 / 2.80	
RW22 (MAP)	2180 MSL	227.33	
2180 MSL	ULOYO (DF) (FO) (RNP 1.00)		4000

CITY AND STATE
ABILENE, TX

ELEVATION: 1791 **TDZE: 1764**
AIRPORT NAME:
ABILENE RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 22, ORIG-A, 01/05/2017

SUP: **19**
AMDT: **ORIG**
DATED: **01/15/2009**

QUALITY
19
CHECKED