

U.S. Department of Transportation Federal Aviation Administration		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES					MISSED APPROACH										
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW32 CLIMB TO 3600 DIRECT WOGAN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW WOGAN, RT, 142.11 INBOUND CHART FAS OBST: 1536 TOWER 321137N/0980808W ROUTE TYPE DESCRIPTION: A,P APPROACH ROUTE QUALIFIER 2: S CHART VDP AT 1.52 MILES TO RW32 CUGOR TO RWY 32: 3.04/40 MAG VAR: 7E EPOCH YEAR: 90											
WINIT (IAF) (40E) (43A)	HOVIR (NOPT) (TF) (FB) (40E) (41E) (43B)	052.19/5.00	3600												
COVON (IAF) (40E) (43A)	HOVIR (NOPT) (TF) (FB) (40E) (41E) (43B)	232.33/5.00	3600												
HOVIR (IF/IAF) (40E) (43I)	CUGOR (TF) (FB) (40E) (43F)	322.24/6.01	3000												
RW32 (MAP) (40G) (41Y) (43M)	1721 MSL (CA) (42M)	322.21													
1721 MSL	WOGAN (DF)(FO) (40E) (41E) (43H)		3600												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SE HOVIR, RT, 322.24 INBOUND, 3600 FT IN LIEU OF PT (IAF)(40E)(41E)(43C) 3. FAC: 322.21 FAF: CUGOR _____ DIST FAF TO MAP: 5.17 THLD: 5.17 4. MIN. ALT: HOVIR 3600, CUGOR 3000 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: 34:1 IS CLEAR 8. MSA FROM: _____															
MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	STANDARD									
CATEGORY ==>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
LNAV MDA	1820	1	507	1820	1	507	1820	1 1/2	507	1820	1 1/2	507			
CIRCLING	1820	1	499	1820	1	499	1820	1 1/2	499	1960	2	639			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA.															
CITY AND STATE			ELEVATION: 1321 TDZE: 1313		FACILITY IDENTIFIER:		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:			SUP:					
STEPHENVILLE, TX			AIRPORT NAME: CLARK FIELD MUNI		RNAV		OCT 27 2005 RNAV (GPS) RWY 32, ORIG			AMDT: NONE					
										DATE					

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA AREA

FROM	TO	ALTITUDE
1. 232/30 CW 052/30	HOVIR (IF/IAF) (NOPT)	3600
2. 052/30 CW 142/30	WINIT (IAF)	3600
3. 142/30 CW 232/30	COVON (IAF)	3600

CITY AND STATE

STEPHENVILLE, TX

ELEVATION:

1321 TDZE:

1313

AIRPORT NAME:

CLARK FIELD MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

OCT 27 2005

RNAV (GPS) RWY 32, ORIG

SUP:

AMDT: NONE

DATED: