

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW08  CLIMB TO 3000 DIRECT ASARE AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD E, RT, 257.59 INBOUND. CHART FAS OBST: 1419 TREE 444721N/0894027W DISTANCE TO THLD FROM 200 HAT: 0.46 NM. CHART VDP AT 1.10 NM TO RW08* *LNAV ONLY. WAAS CHANNEL # 42820 REFERENCE PATH ID: W08A CHART CIRCLING ICON. LTP HAE: 352.9 M									
RROBB		PLEAD (TF) (FO) (RNP 2.00)			302.68 / 21.43			3000											
BELGO (IAF)		PLEAD (NOPT) (TF) (FB) (RNP 1.00)			076.84 / 19.81			3000											
MAXMA (IAF)		PLEAD (NOPT) (TF) (FB) (RNP 1.00)			119.54 / 16.42			3000											
PLEAD (IF/IAF)		HENPA (TF) (FB) (RNP 1.00)			077.17 / 6.89			3000											
HENPA (FAF)		WOKOS/2.00 NM TO RW08 (TF) (FB) (RNP 0.30)			077.29 / 3.25														
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W PLEAD, RT, 077.17 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 077.29 FAF: HENPA DIST FAF TO MAP: 5.25 THLD: 5.25 4. MIN. ALT: PLEAD 3000, HENPA 3000, WOKOS/2.00 NM TO RW08 1960* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 3000 GS ALT AT: HENPA 3000 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 56.3 34:1 IS CLEAR 8. MSA FROM: RW08 3600																MAG VAR: 0E		EPOCH YEAR: 1985	
<b>MINIMUMS</b>																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD									
CATEGORY >>>>>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	1474	1/2	200	1474	1/2	200	1474	1/2	200	1474	1/2	200							
LNAV/VNAV DA	1601	5/8	327	1601	5/8	327	1601	5/8	327	1601	5/8	327							
LNAV MDA	1680	1/2	406	1680	1/2	406	1680	3/4	406	1680	3/4	406							
CIRCLING	1740	1	463	1740	1	463	1740	1 1/2	463	1840	2	563							
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C (2F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT MAXMA ON V26 WESTBOUND.																			
CITY AND STATE MOSINEE, WI		ELEVATION: 1277 TDZE: 1274 AIRPORT NAME: CENTRAL WISCONSIN			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 8, AMDT 1C 17 AUGUST 2017					SUP:							
												AMDT: 1B							
												DATED 07/23/2015							



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
WOKOS/2.00 NM TO RW08	RW08 (MAP) (TF) (FO) (RNP 0.30)	077.29 / 2.00	
RW08 (MAP)	1474 MSL (CA)	077.29	
1474 MSL	ASARE (DF) (FO) (RNP 1.00)		3000

QUALITY  
16  
CHECKED

CITY AND STATE  
MOSINEE, WI

ELEVATION: 1277 TDZE: 1274  
AIRPORT NAME:  
CENTRAL WISCONSIN

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 8, AMDT 1C  
17 AUGUST 2017

SUP:  
AMDT: 1B  
DATED: 07/23/2015