U.S. Department of Transportation
Federal Aviation Administration

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
JINAK WP (IAF)	PURIC WP (TF) (FB) (NOPT)	099.26/15.54	2500
KINDE WP (IAF)	PURIC WP (TF) (FB) (NOPT)	347.14/10.43	2500
PURIC WP (IF/IAF)	NOBIC WP (TF) (FB)	073.51/6.00	2400
RW07 (MAP)	1200 MSL (CA)	073.59	
1200 MSL	DOYET WP (DF) (FO)		2500
PROCEDURE NA FOR ARRIVAL VIA V-47 SOUTHBOUND	AT JINAK VIA V-38 WESTBOUND	AND FOR ARRIVAL AT KINDE	

MISSED APPROACH

GLS: NA LNAV/VNAV: DA

LNAV: RW07

CLIMB TO 2500 DIRECT DOYET WP AND HOLD

ADDITIONAL FLIGHT DATA:

HOLD E, RT, 253.83 INBOUND
FAS OBST: 952 GRAIN ELEVATOR 410027/834234
*CHART VDP AT 1.34 NM TO RW07
DISTANCE TO THLD FROM 391 HAT: 1.15 NM
FINAL SEGMENT (TF)

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD W PURIC WP, RT, 073.51 INBOUND, 2500 FT IN LIEU OF PT (IAF)
3. FAC: 073.59 FAF: NOBIC WP DIST FAF TO MAP: 4.85 THLD: 4.85
4. MIN. ALT: PURIC WP 2500, NOBIC WP 2400
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: 2400 GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: 3.00 TCH: 39.0 34:1 IS CLEAR
8. MSA FROM: RW07 2900

MAG VAR: 5W EPOCH YEAR: 85

MINIMUMS

TAKEOFF: [X] STANDARD [ ] SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A [X]

CATEGORY =====>	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
GLS PA DA		NA			NA			NA			NA				
LNAV/VNAV DA	1200	1 1/2	391	1200	1 1/2	391	1200	1 1/2	391	1200	1 1/2	391			
LNAV MDA	1260	1	451	1260	1	451	1260	1 1/4	451	1260	1 1/2	451			
CIRCLING	1440	1 1/2	627	1440	1 1/2	627	1440	1 3/4	627	1440	2	627			

NOTES: *LNAV ONLY
GPS OR RNP-0.3 REQUIRED. DME/DME RNP -0.3 NA. BARO VNAV NA BELOW -16 (4F)
IF LOCAL ALTIMETER SEETING NOT RECEIVED, USE LIMA ALLEN COUNTY ALTIMETER SETTING AND INCREASE DA TO 1280 FEET, INCREASE ALL MDAs 80 FEET.
BARO VNAV AND VDP NA WITH LIMA ALLEN COUNTY ALTIMETER SETTING.

CITY AND STATE	ELEVATION: 813 TDZE: 809 AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
FINDLAY, OH	FINDLAY	RNAV	NOV 25 2004 RNAV (GPS) RWY 7, ORIG	AMDT: NONE DATE