

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
AMBLR	THREE	AMBLR3.AMF	TWO	07/21/2016	10 OCT 2019
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 10: CLIMB ON HEADING 103.57 TO 705, THEN DIRECT GIMOW THEN ON DEPICTED ROUTE, THENCE...

TAKEOFF RWY 28: CLIMB ON HEADING 283.59 TO 705, THEN DIRECT EGIXE THEN ON DEPICTED ROUTE, THENCE...

...MAINTAIN 4000 OR AS ASSIGNED BY ATC.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: GPS REQUIRED

NOTE: RNAV 1

TAKEOFF MINIMUMS:

RWY 10, 28 : STANDARD

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:**LOST COMMUNICATIONS PROCEDURES:****ADDITIONAL FLIGHT DATA:**

CHART: HOLDING PATTERN AT AMF NDB, HOLD SW RT, 046.87 INBOUND, 5 DME

CHART: TOP ALTITUDE: ASSIGNED BY ATC

REFERENCE MAG VAR: PAGH 13E EPOCH YR: 2020

DME/DME ASSESMENT: NOT CONDUCTED

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
SHUNGNAC (PAGH)	SHUNGNAC	AK

COMMUNICATIONS:

ZAN, CTAF



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
AMBLR	THREE	AMBLR3.AMF	TWO	07/21/2016	10 OCT 2019

FIXES AND/OR NAVAIDS:

AMF NDB
IRSAW
JAGTI

REMARKS:**FLIGHT INSPECTED BY:**

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018. SUBJECT: FLIGHT INSPECTION REVIEW NOT REQUIRED.

OFFICE SYMBOL:**DATE:****DEVELOPED BY:**

LEO J. PALMER

Digitally signed by

LEO PALMER

Jun 06, 2019

OFFICE SYMBOL:

AJV-A421

DATE:

03/28/2019

APPROVED BY:

MARLON ROBINSON

OFFICE SYMBOL:

AJV-A420

DATE:**REQUIRED EFFECTIVE DATE:**

ROUTINE

COORDINATED WITH:

<u>A4A</u>	<u>ALPA</u>	<u>AOPA</u>	<u>APA</u>	<u>HAI</u>	<u>NBAA</u>
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ARPT MGR, ZAN

CHANGES - REASONS:

1. ALL REFERENCES TO RWY 9/27 HAVE BEEN CHANGED TO RWY 10/28. - AIRPORT MAGVAR UPDATE.
2. DP ROUTE DESCRIPTIONS CHANGED FROM "TAKEOFF RWY 9: CLIMB TO 4000 OR ATC ASSIGNED HIGHER ALTITUDE DIRECT GIMOW AND VIA TRACK 187.76 TO IRSAW, AND VIA TRACK 277.57 TO JAGTI, AND VIA TRACK 321.86 TO AMF NDB/DME.". AND "TAKEOFF RWY 27: CLIMB TO 4000 OR ATC ASSIGNED HIGHER ALTITUDE DIRECT EGIXE AND VIA TRACK 293.72 TO AMF NDB/DME." TO "TAKEOFF RWY 10: CLIMB ON HEADING 103.67 TO 705, THEN DIRECT GIMOW THEN ON DEPICTED ROUTE, THENCE..." AND "TAKEOFF RWY 28: CLIMB ON HEADING 283.52 TO 705, THEN DIRECT EGIXE THEN ON DEPICTED ROUTE, THENCE..." ...MAINTAIN 4000 OR AS ASSIGNED BY ATC." - UPDATED TERMINOLOGY IAW 8260.48G.
3. REFERENCE MAGVAR CHANGED FROM 19E/2005 TO 13E/2020. - AIRPORT MAGVAR UPDATE.
4. CHART HOLDING MOVED FROM "FIXES AND OR NAVAIDS" TO "ADDITIONAL FLIGHTDATA" - IAW 8260.46G APPENDIX D.
5. ADDED LNAV ENGAGEMENT LEG TO DEPARTURE (DATA RECORD). - IAW 8260.46G



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME							NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
AMBLR							THREE	AMBLR3.AMF	TWO	07/21/2016	10 OCT 2019
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS		
RW10 (AER)	665325.88N-1571029.44W	N									
705 MSL				VA	116.57						
GIMOW	665054.07N-1565740.67W	Y	FO	DF							
IRSAW	664055.67N-1571021.54W	Y	FB	TF	206.76	11.20					
JAGTI	664521.48N-1573255.05W	Y	FB	TF	296.57	10.00					
AMF NDB	670618.87N/1575136.54W	Y	FB	TF	340.86	22.28					
RW28 (AER)	665308.27N-1570859.85W	N									
705 MSL				VA	296.59						
EGIXE	665539.26N-1572150.84W	Y	FB	DF							
AMF NDB	670618.87N/1575136.54W	Y	FO	TF	312.73	15.84					

