

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO			COURSE AND DISTANCE			ALTITUDE		MAP: LVT R-107/28.90 DME									
LVT VOR/DME (IAF)		LARRY/20.00 DME			107.00 / 20.00			3500		CLIMB TO 2500 THEN CLIMBING RIGHT TURN TO 3500 ON LVT VOR/DME R-107 TO LARRY/20.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD W, RT, 107.00 INBOUND. CHART FAS OBST: 1719 TREE 362829N/0843727W CHART 1660 POWERLINE TOWER 362645N/0843603W. CHART LVT R-024 AT LVT VOR/DME. CHART LVT R-171 AT LVT VOR/DME. CHART CIRCLING ICON. FAC ALIGNS TO CENTER OF LANDING AREA.									
LVT VOR/DME/LVT 20.00 DME CW (IAF)		LARRY/20.00 DME			20.00 DME ARC			3500											
LVT VOR/DME/LVT 20.00 DME CCW (IAF)		LARRY/20.00 DME			20.00 DME ARC			3500											
LARRY/20.00 DME (IF)		LVT VOR/DME R-107/25.00 DME			107.00 / 5.00			3200											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 2W EPOCH YEAR: 1985									
2. PROFILE STARTS AT LARRY																			
3. FAC 107.00 FAF LVT VOR/DME R-107/25.00 DME DIST FAF TO MAP _____ THLD _____																			
4. MIN. ALT LARRY 3500, LVT VOR/DME R-107/25.00 DME 3200																			
8. MSA FROM: LVT VOR/DME 090-270 3900, 270-090 3000 (30 NM)																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		X							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
CIRCLING		2040	1	495	2040	1 1/4	495	2200	1 3/4	655	2260	2 1/4	715						
NOTES: CHART NOTE: CIRCLING TO RWY 5 NA AT NIGHT. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MONTICELLO ALTIMETER SETTING AND INCREASE ALL MDA 240 FEET AND CIRCLING CAT C 1 SM, CAT D 3/4 SM.																			
CITY AND STATE ONEIDA, TN		ELEVATION: 1545 TDZE: AIRPORT NAME: SCOTT MUNI			FACILITY IDENTIFIER: LVT			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME-A, AMDT 5D 5 JANUARY 2017						SUP AMDT 5C DATE 02/04/2016					