

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CODKI (IAF)	ILICA (NOPT) (FB)	210.54 / 5.00	3000	LNAV: RW12
EMIBY (IAF)	ILICA (NOPT) (FB)	030.46 / 5.00	3000	
ILICA (IF/IAF)	WLCHS (FB)	120.50 / 6.04	2800	CLIMB TO 3000 DIRECT SAJSI AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD SE, RT, 300.82 INBOUND. CHART FAS OBST: 1462 TOWER 443313N/0893528W WLCHS TO RW12: 3.05/40.

- PT        SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
- HOLD NW ILICA, RT, 120.50 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 120.59 FAF: WLCHS DIST FAF TO MAP: 5.12 THLD: 5.12
- MIN. ALT: ILICA 3000, WLCHS 2800, HIRDA/2.30 NM TO RW12 1880
- DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT:
- MIN GS INCPT:        GS ALT AT:        OM:        MM:        IM:
- GS ANGLE:        TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 1W EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1760	1	652	1760	1	652	1760	1 3/4	652	1760	2	652			
CIRCLING	1760	1	650	1760	1	650	1760	1 3/4	650	1800	2 1/4	690			

NOTES:  
CHART NOTE: DME/DME RNP-0.3 NA.  
CHART NOTE: PROCEDURE NA AT NIGHT.  
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.  
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MOSINEE ALTIMETER SETTING AND INCREASE  
SEE 8260-10

@ CAT D 800-2 1/4  
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE STEVENS POINT, WI	ELEVATION: 1110 TDZE: 1108 AIRPORT NAME: STEVENS POINT MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 11 FEB 2010	SUP: AMDT: NONE DATED
-------------------------------------	---	---------------------------------	--	-----------------------------

RNAV (GPS) - STANDARD  
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES CONT.

ALL MDA 60 FEET, INCREASE LNAV CAT C AND D VISIBILITY 1/4 MILE AND CIRCLING CAT C AND D VISIBILITY 1/4 MILE.

## TAA

	FROM	TO	ALT
1.	030/30 CW 211/30 (NOPT)	030/12 CW 211/12	3600
2.	030/12 CW 211/12	ILJCA (IF/IAF) (FB)	3000
3.	211/30 CW 301/30	211/8 CW 301/8	3500
4.	211/8 CW 301/8	CODKI (IAF) (FB)	3000
5.	301/30 CW 030/30	EMIBY (IAF) (FB)	3000

CITY AND STATE

STEVENS POINT, WI

ELEVATION: 1110 TDZE: 1108

AIRPORT NAME:

STEVENS POINT MUNI

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY  
1  
OFFICE

CITY AND STATE  STEVENS POINT, WI	ELEVATION: 1110    TDZE: 1108  AIRPORT NAME:  STEVENS POINT MUNI	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 12, ORIG  11 FEB 2010	SUP:
				AMDT:        NONE
				DATED: