

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
REKTE (IAF)	SAJSI (NOPT) (FB)	210.86 / 5.00	3000	LNAV: RW30
TIVDE (IAF)	SAJSI (NOPT) (FB)	030.78 / 5.00	3000	
SAJSI (IF/IAF)	WEDNE (FB)	300.82 / 6.04	2800	CLIMBING LEFT TURN TO 3000 DIRECT SAJSI AND HOLD.
				ADDITIONAL FLIGHT DATA: CHART FAS OBST: 1229 TREE 443158N/0892857W WEDNE TO RW30: 3.04/40.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD SE SAJSI, RT, 300.82 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 300.73 FAF: WEDNE DIST FAF TO MAP: 5.13 THLD: 5.13
- MIN. ALT: SAJSI 3000, WEDNE 2800, JIBSU/2.00 NM TO RW30 1780
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 1W

EPOCH YEAR: 1995

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @									
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1520	1	412	1520	1	412	1520	1 1/4	412	1520	1 1/4	412			
CIRCLING	1580	1	470	1580	1	470	1660	1 1/2	550	1800	2 1/4	690			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: PROCEDURE NA AT NIGHT.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MOSINEE ALTIMETER SETTING AND INCREASE
SEE 8260-10

@ CAT D 800-2 1/4
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
2
RECORD

CITY AND STATE STEVENS POINT, WI	ELEVATION: 1110 TDZE: 1108 AIRPORT NAME: STEVENS POINT MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30, ORIG 11 FEB 2010	SUP: AMDT: NONE DATED
-------------------------------------	---	---------------------------------	--	-----------------------------

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

ALL MDA 60 FEET, INCREASE LNAV CAT D VISIBILITY 1/4 MILE AND CIRCLING CAT C AND D VISIBILITY 1/4 MILE.

TAA

	FROM	TO	ALT
1.	211/30 CW 031/30 (NOPT)	SAJSI (IF/IAF) (FB)	3000
2.	031/30 CW 121/30	TIVDE (IAF) (FB)	3000
3.	121/30 CW 211/30	121/13 CW 211/13	3600
4.	121/13 CW 211/13	REKTE (IAF) (FB)	3000

CITY AND STATE

STEVENS POINT, WI

ELEVATION: 1110 TDZE: 1108

AIRPORT NAME:

STEVENS POINT MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 30, ORIG

11 FEB 2010

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
SERVED

CITY AND STATE STEVENS POINT, WI	ELEVATION: 1110 TDZE: 1108 AIRPORT NAME: STEVENS POINT MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 30, ORIG 11 FEB 2010	SUP: AMDT: NONE DATED:
-------------------------------------	---	---------------------------------	--	------------------------------