

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97. 23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH											
FROM		TO			COURSE AND DISTANCE				ALTITUDE		MAP: 5.62 MILES AFTER MIXED OR AT FNT 21.62 DME.										
FNT VORTAC (IAF) COLBA		COLBA INT / FNT 10.00 DME			080.00 / 10.00				3000		CLIMBING LEFT TURN TO 2500 VIA FNT R-080 TO MIXED INT/FNT 16.00 DME AND HOLD.										
		MIXED INT / FNT 16.00 DME			080.00 / 6.00				2500												
										ADDITIONAL FLIGHT DATA: HOLD W, LT, 080.00 INBOUND FAS OBST: 1085 TOWER 430417 / 831853											
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT COLBA 3. FAC <u>080.00</u> FAF <u>MIXED</u> DIST FAF TO MAP <u>5.62</u> THLD <u>-</u> 4. MIN. ALT <u>COLBA 3000, MIXED 2500</u> 8. MSA FROM: <u>FNT VORTAC 3100</u>										MAG VAR: 6W EPOCH YEAR: 00											
MINIMUMS																					
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15 FOR THIS AIRPORT								ALTERNATE: N A		X					
CATEGORY		A			B			C			D			E							
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA					
CIRCLING		1460	1	616	1460	1 1/4	616	1460	1 3/4	616		NA									
NOTES: USE FLINT ALTIMETER SETTING. CAUTION: NE/SW DRAG STRIP 2 MILES NORTH OF AIRPORT.																					
CITY AND STATE				ELEVATION: 844 TDZE:				FACILITY IDENTIFIER:				PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:				SUP					
LAPEER, MI				DUPONT - LAPEER				FNT				21 FEB 2002 VOR-A, ORIG				AMDT 12					
																DATED 6/5/86					