

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.

*RNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE KENDALL-TAMiami EXECUTIVE ALTIMETER

SETTING: INCREASE LPV DA TO 283; INCREASE RNAV/VNAV DA TO 283; INCREASE ALL MDA 40 FEET.

QUALITY
CHECKED

CITY AND STATE
HOMESTEAD, FL

ELEVATION: 7 THRE: 6
AIRPORT NAME:
HOMESTEAD GENERAL AVIATION

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 10, ORIG
25 AUG 2011

SUP:
AMDT: NONE
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

| | |
|--|---------------|
| OPERATION TYPE | 0 |
| SBAS SERVICE PROVIDER IDENTIFIER | 0 |
| AIRPORT IDENTIFIER | X51 |
| RUNWAY | RW10 |
| APPROACH PERFORMANCE DESIGNATOR | 0 |
| ROUTE INDICATOR | |
| REFERENCE PATH DATA SELECTOR | 0 |
| REFERENCE PATH IDENTIFIER (APPROACH ID) | W10A |
| LTP/FTP LATITUDE | 253009.8350N |
| LTP/FTP LONGITUDE | 0803318.3515W |
| LTP/FTP ELLIPSOIDAL HEIGHT | -00228 |
| FPAP LATITUDE | 253010.3100N |
| FPAP LONGITUDE | 0803139.8700W |
| THRESHOLD CROSSING HEIGHT (TCH) | 00040.0 |
| TCH UNITS SELECTOR (METERS OR FEET USED) | F |
| GLIDEPATH ANGLE (GPA) | 03.00 |
| COURSE WIDTH AT THRESHOLD | 106.75 |
| LENGTH OFFSET | 1832 |
| HORIZONTAL ALERT LIMIT (HAL) | 40.0 |
| VERTICAL ALERT LIMIT (VAL) | 50.0 |

CRC REMAINDER

45F30B4F

ADDITIONAL PATH POINT RECORD INFORMATION

| | |
|-------------------------|--------|
| ICAO CODE | K7 |
| LTP ORTHOMETRIC HEIGHT | +00018 |
| FPAP ORTHOMETRIC HEIGHT | +00018 |

QUALITY
6
CHECKED

CITY AND STATE

HOMESTEAD, FL

ELEVATION: 7

THRE: 6

AIRPORT NAME:

HOMESTEAD GENERAL AVIATION

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 10, ORIG

25 AUG 2011

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

| SEGMENT | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 |
|------------------|--------|------|-------------|-------|-------|------------|----------|---|------------|-------|-------------|------|---|
| SUSAP X51 K7FR10 | ADVALL | 010D | VALLK7EA0E | A | IF | | | | | 18000 | | A JS | I |
| SUSAP X51 K7FR10 | ADVALL | 020H | OLMUK7EA0EE | B | 010TF | | 09930135 | + | 02000 | | A JS | I | |
| SUSAP X51 K7FR10 | AFAMIN | 010F | AMINK7EA0E | | IF | | | | | 18000 | | A JS | I |
| SUSAP X51 K7FR10 | AFAMIN | 020H | OLMUK7EA0EY | | 020TF | | 14290069 | + | 02000 | | A JS | I | |
| SUSAP X51 K7FR10 | AFAMIN | 030H | OLMUK7EA0EE | AR | HF | | 09560040 | + | 02000 | | A JS | I | |
| SUSAP X51 K7FR10 | R | 010H | OLMUK7EA0E | I | IF | | | + | 02000 | 18000 | | A JS | I |
| SUSAP X51 K7FR10 | R | 020W | EMBAK7EA1E | F | 051TF | | 09560061 | + | 01500 | | XAGUH K7EAA | JS | I |
| SUSAP X51 K7FR10 | R | 020W | EMBAK7EA2 | WALPV | | ALNAV/VNAV | ALNAV | | | | | JS | I |
| SUSAP X51 K7FR10 | R | 021Y | IYNUK7EA0E | S | 031TF | | 09570020 | V | 0086000873 | -300 | | A JS | I |
| SUSAP X51 K7FR10 | R | 030X | AGUHK7EA0EY | M | 031TF | | 09570021 | | 00205 | -300 | | A JS | I |
| SUSAP X51 K7FR10 | R | 040 | | 0 | M | CA | 0957 | + | 00500 | | | A JS | I |
| SUSAP X51 K7FR10 | R | 050H | OLMUK7EA0EY | L | DF | | | + | 02000 | | | A JS | I |
| SUSAP X51 K7FR10 | R | 060H | OLMUK7EA0EE | R | HM | | 09560040 | + | 02000 | | | A JS | I |

QUALITY
6
CHECKED

FAA FORM 8260-10 /April 2006 (Computer Generated)

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

6
CHECKED

| | | | | | | |
|-------------------------------------|----------------------------|---------|-------------------------------------|--|--------|------|
| CITY AND STATE HOMESTEAD, FL | ELEVATION: 7 | THRE: 6 | FACILITY IDENTIFIER: RNAV | PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, ORIG 25 AUG 2011 | SUP: | |
| | AIRPORT NAME: | | | | AMDT: | NONE |
| | HOMESTEAD GENERAL AVIATION | | | | DATED: | |