

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
HOMESTEAD, FL	HOMESTEAD GENERAL AVIATION	25 AUG 2011	ORIG

TAKEOFF MINIMUMS:

RWY 1, 10, 19, 28 STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 1 – CLIMB ON A HEADING BETWEEN 186 CW 046 FROM DEPARTURE END OF RUNWAY OR MINIMUM CLIMB OF 461 FT PER NM TO 2500 FOR HEADINGS 047 THROUGH 185.

RWY 10 – CLIMB ON A HEADING BETWEEN 096 CW 275 FROM DEPARTURE END OF RUNWAY OR MINIMUM CLIMB OF 512 FT PER NM TO 2500 FOR HEADINGS 276 THROUGH 095.

RWY 19 – CLIMB HEADING 185.49 TO 1100 BEFORE PROCEEDING NORTH OR NORTHEAST.

RWY 28 – CLIMB HEADING 275.69 TO 1100 BEFORE PROCEEDING EAST OR NORTHEAST.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 1, FENCE 231 FT FROM DER, 457 FT LEFT OF CENTERLINE, 5 FT AGL/14 FT MSL.

NOTE: RWY 10, BUILDING 170 FT FROM DER, 415 FT RIGHT OF CENTERLINE, 17 FT AGL/26 FT MSL.

NOTE: RWY 28, LIGHT POLE 118 FT FROM DER, 371 FT LEFT OF CENTERLINE, 26 FT AGL/35 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT:

RWY 1, 10, 19, 28: 1849 FT MSL TOWER 253225.39N/0802806.20W.

