

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: DXX NDB									
ARDUE INT			DXX NDB			256.64 / 20.83			3000		CLIMB TO 2200 THEN CLIMBING LEFT TURN TO 2700 DIRECT DXX NDB AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, LT, 309.00 INBOUND. CHART FAS OBST: 1209 TREE 445701N/0961007W FAC CROSSES RWY C/L EXTENDED 2922 FROM THLD.									
ATY VORTAC			DXX NDB			080.28 / 41.01			4000											
RWF VOR/DME			DXX NDB			297.98 / 54.61			3000											
1. PT <u> R </u> SIDE OF COURSE <u> 129.00 </u> OUTBOUND <u> 2600 </u> FT WITHIN <u> 10 </u> MILES OF <u> </u> DXX NDB (IAF) 2. _____ 3. FAC <u> 309.00 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT <u> ANTOI INT 1700* </u> 8. MSA FROM: <u> DXX NDB 3400 </u>										MAG VAR: 3E EPOCH YEAR: 2015										
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A					STANDARD @					
CATEGORY ==>		A			B			C			D			E						
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-32		1700	1	622	1700	1	622	1700	1 3/4	622			NA							
CIRCLING		1700	1	617	1700	1	617	1700	1 3/4	617			NA							
ANTOI FIX MINIMUMS																				
S-32		1520	1	442	1520	1	442	1520	1 3/8	442			NA							
CIRCLING		1640	1	557	1640	1	557	1640	1 1/2	557			NA							
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE APPLETON MUNI ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET AND VISIBILITY CAT C TO 2 MILES, ANTOI FIX MINIMUMS INCREASE CIRCLING CAT C VISIBILITY TO 1 3/4 MILE. *1760 WHEN USING APPLETON MUNI ALTIMETER SETTING.																				
CITY AND STATE MADISON, MN		ELEVATION: 1083 THRE: 1078 AIRPORT NAME: LAC QUI PARLE COUNTY			FACILITY IDENTIFIER: DXX		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 32, AMDT 4 15 NOVEMBER 2012					SUP NDB OR GPS AMDT 3A DATE 2/19/98								