

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
WENPO (IAF)	IXMIX (NOPT) (FB)	077.58 / 5.00	2400	LNAV: RW35	
YIKUL (IAF)	IXMIX (NOPT) (FB)	257.68 / 5.00	2400	CLIMBING RIGHT TURN TO 2400 DIRECT IXMIX AND HOLD.	
IXMIX (IF/IAF)	HOTOW (FB)	347.63 / 6.10	2100	ADDITIONAL FLIGHT DATA: CHART FAS OBST: 659 TREE 335007N/0880641W CHART COLUMBUS 1 MOA. HOTOW TO RW35: 3.04/40. CHART COLUMBUS AFB ATIS	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S IXMIX, RT, 347.63 INBOUND, 2400 FT. IN LIEU OF PT (IAF)
- FAC: 347.61 FAF: HOTOW DIST FAF TO MAP: 4.97 THLD: 4.97
- MIN. ALT: IXMIX 2400, HOTOW 2100, JIVAR/2.00 NM TO RW35 1120
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 2W

EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:	<input type="checkbox"/>	STANDARD	<input checked="" type="checkbox"/>	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	<input checked="" type="checkbox"/>											
CATEGORY	=====	A			B			C			D			E			
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA		1000	1	537	1000	1	537	1000	1 1/2	537	1000	1 3/4	537				
CIRCLING		1100	1	637	1100	1	637	1100	1 3/4	637	1100	2	637				

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA.
CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: USE COLUMBUS AFB ALTIMETER SETTING; WHEN NOT RECEIVED USE GOLDEN TRIANGLE RGNL
ALTIMETER SETTING AND INCREASE ALL MDA 40 FT AND CIRCLING CATS C/D VISIBILITY 1/4 MILE.

CITY AND STATE VERNON, AL	ELEVATION: 463 TDZE: 463 AIRPORT NAME: LAMAR COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 29 JUL 2010	SUP: AMDT: NONE DATED
------------------------------	---	------------------------------	--	-----------------------------

QUALITY
CHECKED

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	258/30 CW 078/30 (NOPT)	IXMIX (IF/IAF) (FB)	2400
2.	078/30 CW 168/30	WENPO (IAF) (FB)	2400
3.	168/30 CW 258/30	YIKUL (IAF) (FB)	2400

QUALITY
A
CHECKED

CITY AND STATE
VERNON, AL

ELEVATION: 463 TDZE: 463
AIRPORT NAME:
LAMAR COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 35, ORIG
29 JUL 2010

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
4
CHECKED

CITY AND STATE VERNON, AL	ELEVATION: 463 TDZE: 463 AIRPORT NAME: LAMAR COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, ORIG 29 JUL 2010	SUP:
				AMDT: NONE
				DATED: