

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
<b>US DEPARTMENT OF TRANSPORTATION</b> <b>FEDERAL AVIATION ADMINISTRATION</b>			
<b>TERMINAL ROUTES</b>		<b>MISSED APPROACH</b>	
<b>FROM</b> SLN VORTAC (IAF) ZANPU (IF) YISYU (FAF) UMH0Y/1.90 NM TO RW36 RW36 (MAP) 1920 MSL	<b>TO</b> ZANPU (FB) YISYU (FB) UMH0Y/1.90 NM TO RW36 (FB) RW36 (MAP) (FO) 1920 MSL FEBNO (FO)	<b>COURSE AND DISTANCE</b> 350.12 / 42.03 354.51 / 6.20 354.51 / 3.19 354.51 / 1.90 354.51	<b>ALTITUDE</b> 3400 3200 3400
		LP: RW36 LNAV: RW36  CLIMB TO 3400 DIRECT FEBNO AND HOLD.	
		<b>ADDITIONAL FLIGHT DATA:</b> HOLD N, RT, 174.51 INBOUND. CHART FAS OBST: 1615 TREE 394706N/0974000W CHART FAS OBST: 1625 TREE 394737N/0974001W WAAS CHANNEL # 69425 REFERENCE PATH ID: W36A YISYU TO RW36: 3.00/40.6. LTP HAE: 442.1 M	
1. PT <u>      </u> SIDE OF COURSE <u>      </u> OUTBOUND <u>      </u> FT WITHIN <u>      </u> MILES OF <u>      </u> (IAF)			
2. PROFILE STARTS AT ZANPU			
3. FAC: <u>354.51</u> FAF: <u>YISYU</u> DIST FAF TO MAP: <u>5.09</u> THLD: <u>5.09</u>			
4. MIN. ALT: <u>ZANPU 3400, YISYU 3200, UMH0Y/1.90 NM TO RW36 2180</u>			
5. DIST TO THLD FROM OM: <u>      </u> MM: <u>      </u> IM: <u>      </u> 150 HAT: <u>      </u> 100 HAT: <u>      </u> GS ANT: <u>      </u>			
6. MIN GS INCPT: <u>      </u> GS ALT AT: <u>      </u> OM: <u>      </u> MM: <u>      </u> IM: <u>      </u>			
7. GS ANGLE: <u>      </u> TCH: <u>34:1 IS NOT CLEAR</u>			
8. MSA FROM: <u>RW36 3900</u>		MAG VAR: <u>7E</u> EPOCH YEAR: <u>1985</u>	
<b>MINIMUMS</b>			
TAKEOFF: <u>SEE FAA FORM 8260-15A FOR THIS AIRPORT</u>		ALTERNATE: <u>N A</u> <input checked="" type="checkbox"/> <u>X</u>	
<b>CATEGORY =====&gt;</b>	<b>A</b>		<b>B</b>
<b>DH/MDA</b>	<b>VIS</b>	<b>HAT/HAA</b>	<b>DH/MDA</b>
<b>LP MDA</b>	1920	1	382
<b>LNAV MDA</b>	1920	1	382
<b>CIRCLING</b>	2020	1	482
<b>C</b>			
<b>DH/MDA</b>	<b>VIS</b>	<b>HAT/HAA</b>	<b>DH/MDA</b>
1920	1 1/8	382	1920
1920	1 1/8	382	1920
2020	1 1/2	482	2020
<b>D</b>			
<b>DH/MDA</b>	<b>VIS</b>	<b>HAT/HAA</b>	<b>DH/MDA</b>
NA	NA	NA	NA
NA	NA	NA	NA
NA	NA	NA	NA
<b>E</b>			
<b>DH/MDA</b>	<b>VIS</b>	<b>HAT/HAA</b>	<b>DH/MDA</b>
NA	NA	NA	NA
NA	NA	NA	NA
NA	NA	NA	NA
<b>NOTES:</b> CHART NOTE: WHEN VGSI INOP, CIRCLING RWY 18 NA AT NIGHT. CHART NOTE: USE CONCORDIA ALTIMETER SETTING; WHEN NOT RECEIVED, USE HEBRON ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET. CHART NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 36 PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)			
<b>CITY AND STATE</b> BELLEVILLE, KS	<b>ELEVATION:</b> 1538 <b>THRE:</b> 1538 <b>AIRPORT NAME:</b> BELLEVILLE MUNI	<b>FACILITY IDENTIFIER:</b> RNAV	<b>PROCEDURE NO./AMDT NO./EFFECTIVE DATE:</b> RNAV (GPS) RWY 36, ORIG 20 OCT 2011
		<b>SUP:</b>	<b>AMDT:</b> NONE
		<b>DATED</b>	



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
RNAV - STANDARD  
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: DME/DME RNP-0.3 NA.

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON SLN VORTAC AIRWAY RADIALS 273 CW 075.

QUALITY  
CHECKED

CITY AND STATE BELLEVILLE, KS	ELEVATION: 1538 THRE: 1538 AIRPORT NAME: BELLEVILLE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 20 OCT 2011	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRPB
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	394848.9000N
LTP/FTP LONGITUDE	0973937.7600W
LTP/FTP ELLIPSOIDAL HEIGHT	+04421
FPAP LATITUDE	395018.0400N
FPAP LONGITUDE	0973934.7100W
THRESHOLD CROSSING HEIGHT (TCH)	00040.6
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1680
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

**CRC REMAINDER**

C8A1ABF1

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04688
FPAP ORTHOMETRIC HEIGHT	+04688

QUALITY  
CHECKED

CITY AND STATE

BELLEVILLE, KS

ELEVATION: 1538

THRE: 1538

AIRPORT NAME:

BELLEVILLE MUNI

FACILITY  
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, ORIG

20 OCT 2011

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**ARINC PACKET - 424-18 - RNAV (GPS)**

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KRPBK3FR36	ASLN	010SLN	K3D 0V	A	IF				18000		A	JS
SUSAP	KRPBK3FR36	ASLN	020ZANPUK3EA0EE	B	010TF		35010420	+ 03400				A	JS
SUSAP	KRPBK3FR36	R	010ZANPUK3EA0E	I	IF			+ 03400		18000		A	JS
SUSAP	KRPBK3FR36	R	020YISYUK3EA1E	F	051TF		35450062	+ 03200			RW36	K3PGA	JS
SUSAP	KRPBK3FR36	R	020YISYUK3EA2WALP			N	ALNAV						JS
SUSAP	KRPBK3FR36	R	021UMHOYK3EA0E	S	031TF		35450032	V 0218002184		-300		A	JS
SUSAP	KRPBK3FR36	R	030RW36	K3PG0GY	M	031TF	35450019	01579		-300		A	JS
SUSAP	KRPBK3FR36	R	040	0	M	CA	3545	+ 01920				A	JS
SUSAP	KRPBK3FR36	R	050FEBNOK3EA0EY		DF			+ 03400				A	JS
SUSAP	KRPBK3FR36	R	060FEBNOK3EA0EE	R	HM		17450040	+ 03400				A	JS

[illegible]

QUALITY  
1  
CHECKED

CITY AND STATE  
BELLEVILLE, KS

ELEVATION: 1538      THRE: 1538  
AIRPORT NAME:  
BELLEVILLE MUNI

**FACILITY IDENTIFIER:**  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 36, ORIG  
20 OCT 2011

SUP:	
AMDT:	NONE
DATED:	

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY  
1  
CHECKED

ELEVATION: 1538      THRE: 1538  
AIRPORT NAME:  
BELLEVILLE MUNI

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 36, ORIG  
20 OCT 2011

SUP:	
AMDT:	NONE
DATED:	