

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION							RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.						
TERMINAL ROUTES														MISSED APPROACH						
FROM				TO			COURSE AND DISTANCE			ALTITUDE		LP: RW04 LNAV: RW04								
JOTPA (IAF)				JAGXA (NOPT) (TF) (FB) (RNP 1.00)			330.42 / 8.70			2500		CLIMB TO 2600 DIRECT JERAL AND HOLD.								
JAGXA (IF/IAF)				LICAJ (TF) (FB) (RNP 1.00)			040.35 / 7.00			2500										
LICAJ (FAF)				WUPGO/2.10 NM TO RW04 (TF) (FB) (RNP 0.30)			040.41 / 2.99													
WUPGO/2.10 NM TO RW04				RW04 (MAP) (TF) (FO) (RNP 0.30)			040.41 / 2.10													
RW04 (MAP)				1243 MSL (CA)			040.41			2600		ADDITIONAL FLIGHT DATA: HOLD NE, RT, 220.56 INBOUND. CHART FAS OBST: 999 POWERLINES 390332N/0841407W CHART FAS OBST: 1019 POWERLINES 390304N/0841422W WAAS CHANNEL # 58327 REFERENCE PATH ID: W04A CHART CIRCLING ICON. LICAJ TO RW04: 3.00/40. CHART CLERMONT COUNTY AWOS-3 FREQUENCY. LTP HAE: 222.2 M								
1243 MSL				JERAL (DF) (FO) (RNP 1.00)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)														MAG VAR: 4W EPOCH YEAR: 1990						
2. HOLD SW JAGXA, RT, 040.35 INBOUND, 2500 FT. IN LIEU OF PT (IAF)																				
3. FAC: 040.41 FAF: LICAJ DIST FAF TO MAP: 5.09 THLD: 5.09																				
4. MIN. ALT: JAGXA 2500, LICAJ 2500, WUPGO/2.10 NM TO RW04 1540																				
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																				
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																				
7. GS ANGLE: _____ TCH: 34:1 IS NOT CLEAR																				
8. MSA FROM: _____																				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A			STANDARD @										
CATEGORY =====>		A			B			C			D			E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
LP MDA	1300	1	460	1300	1	460	1300	1 3/8	460		NA									
LNAV MDA	1320	1	480	1320	1	480	1320	1 3/8	480		NA									
CIRCLING	1360	1	517	1360	1	517	1520	2	677		NA									
NOTES: CHART NOTE: CIRCLING NA AT NIGHT. CHART NOTE: RWY 4/22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). (CONTINUED ON PAGE 2)																				
CITY AND STATE BATAVIA, OH				ELEVATION: 843 TDZE: 840 AIRPORT NAME: CLERMONT COUNTY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1C 22 JUNE 2017					SUP: AMDT: 1B DATED 12/11/2014						

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

**CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CINCINNATI MUNI AIRPORT LUNKEN FIELD
ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND ALL CAT C VISIBILITIES 1/4 SM.**

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	330/30 CW 130/30 (NOPT)	330/20 CW 130/20	2600
2.	330/20 CW 130/20	JAGXA (IF/IAF) (FB)	2500
3.	130/30 CW 220/30	JAGXA (IF/IAF) (FO)	2900
4.	220/30 CW 330/30	220/10 CW 330/10	2700
5.	220/10 CW 330/10	JOTPA (IAF) (FB)	2500

QUALITY
9
CHECKED

CITY AND STATE

BATAVIA, OH

ELEVATION: 843

TDZE: 840

AIRPORT NAME:

CLERMONT COUNTY

 FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, AMDT 1C

22 JUNE 2017

SUP:

AMDT: **1B**DATED: **12/11/2014**

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	I69
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	390431.1930N
LTP/FTP LONGITUDE	0841247.2055W
LTP/FTP ELLIPSOIDAL HEIGHT	+02222
FPAP LATITUDE	390542.9200N
FPAP LONGITUDE	0841139.2200W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1784
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 BECCC926

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02562
FPAP ORTHOMETRIC HEIGHT	+02562

QUALITY
9
CHECKED

CITY AND STATE BATAVIA, OH	ELEVATION: 843 AIRPORT NAME: CLERMONT COUNTY	TDZE: 840 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, AMDT 1C 22 JUNE 2017	SUP:
				AMDT: 1B
				DATED: 12/11/2014