

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW25 CLIMB TO 3000 DIRECT CIMIX AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 066.58 INBOUND. CHART FAS OBST: 1019 TREE 391308N/0821114W DISTANCE TO THLD FROM 200 HAT: 0.49 NM. CHART VDP AT 1.47 NM TO RW25* *LNAV ONLY. WAAS CHANNEL # 90316 REFERENCE PATH ID: W25A CHART CIRCLING ICON. LTP HAE: 197.7 M						
CISBO (IAF)		HOPAX (NOPT) (TF) (FB) (RNP 1.00)			156.82 / 6.50			3000								
DEVAY (IAF)		HOPAX (NOPT) (TF) (FB) (RNP 1.00)			336.91 / 6.50			3000								
HOPAX (IF/IAF)		TACOY (TF) (FB) (RNP 1.00)			246.87 / 6.04			2600								
TACOY (FAF)		ZEPEG/2.17 NM TO RW25 (TF) (FB) (RNP 0.30)			246.80 / 3.45											
ZEPEG/2.17 NM TO RW25 (SEE FORM 8260-10)		RW25 (MAP) (TF) (FO) (RNP 0.30)			246.80 / 2.17											
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE HOPAX, RT, 246.87 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 246.80 FAF: TACOY DIST FAF TO MAP: 5.62 THLD: 5.62 4. MIN. ALT: HOPAX 3000, TACOY 2600, ZEPEG/2.17 NM TO RW25 1500* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2600 GS ALT AT: TACOY 2600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 49.3 34:1 IS CLEAR 8. MSA FROM: _____										MAG VAR: 6W EPOCH YEAR: 1995						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY >>>>>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	965	3/4	200	965	3/4	200	965	3/4	200	965	3/4	200				
LNAV/VNAV DA	1356	2	591	1356	2	591	1356	2	591	1356	2	591				
LNAV MDA	1280	1	515	1280	1	515	1280	1 3/8	515	1280	1 3/8	515				
CIRCLING	1380	1	614	1380	1	614	1420	1 3/4	654	1480	2 1/4	714				
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). @ CAT D 800-2 1/4 CHART NOTE: DME/DME RNP-0.3 NA.																
CITY AND STATE ATHENS/ALBANY, OH		ELEVATION: 766 TDZE: 765 AIRPORT NAME: OHIO UNIVERSITY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2 9 NOVEMBER 2017						SUP:				
												AMDT: 1B				
												DATED 06/25/2015				

QUALITY
 25
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW25 (MAP)	965 MSL (CA)	246.80	

965 MSL	CIMIX (DF) (FO) (RNP 1.00)		3000
---------	----------------------------	--	------

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	157/30 CW 337/30 (NOPT)	HOPAX (IF/IAF) (FB)	3000
2.	337/30 CW 067/30	DEVAY (IAF) (FB)	3000
3.	067/30 CW 157/30	CISBO (IAF) (FB)	3000

QUALITY
25
CHECKED

CITY AND STATE
ATHENS/ALBANY, OH

ELEVATION: 766 TDZE: 765
AIRPORT NAME:
OHIO UNIVERSITY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 25, AMDT 2
9 NOVEMBER 2017

SUP:
AMDT: 1B
DATED: 06/25/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KUNI
RUNWAY	RW25
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W25A
LTP/FTP LATITUDE	391256.3455N
LTP/FTP LONGITUDE	0821314.2900W
LTP/FTP ELLIPSOIDAL HEIGHT	+01977
FPAP LATITUDE	391212.7310N
FPAP LONGITUDE	0821454.2775W
THRESHOLD CROSSING HEIGHT (TCH)	00049.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1048
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0
 <u>CRC REMAINDER</u>	 E3154379

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02318
FPAP ORTHOMETRIC HEIGHT	+02318

QUALITY
25
CHECKED

CITY AND STATE ATHENS/ALBANY, OH	ELEVATION: 766 AIRPORT NAME: OHIO UNIVERSITY	TDZE: 765 	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, AMDT 2 9 NOVEMBER 2017	SUP:
					AMDT: 1B
					DATED: 06/25/2015