

<b>RNAV - STANDARD</b> <b>INSTRUMENT APPROACH PROCEDURE</b> <b>TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW07  CLIMB TO 3000 DIRECT HOPAX AND HOLD.  ADDITIONAL FLIGHT DATA: HOLD NE, RT, 246.87 INBOUND. CHART FAS OBST: 1019 TREE 391209N/0821343W DISTANCE TO THLD FROM 419 HAT: 1.20 NM. CHART VDP AT 1.54 NM TO RW07* *LNAV ONLY. WAAS CHANNEL # 81916 REFERENCE PATH ID: W07A CHART CIRCLING ICON. LTP HAE: 198.4 M							
NETKE (IAF)		CIMIX (NOPT) (TF) (FB) (RNP 1.00)			156.54 / 6.50			3000									
SOYLO (IAF)		CIMIX (NOPT) (TF) (FB) (RNP 1.00)			336.62 / 6.50			3000									
CIMIX (IF/IAF)		FEKLO (TF) (FB) (RNP 1.00)			066.58 / 6.11			2600									
FEKLO (FAF)		UXREL/2.38 NM TO RW07 (TF) (FB) (RNP 0.30)			066.65 / 3.27												
UXREL/2.38 NM TO RW07  (SEE FORM 8260-10)		RW07 (MAP) (TF) (FO) (RNP 0.30)			066.65 / 2.38												
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD SW CIMIX, RT, 066.58 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 066.65 FAF: FEKLO DIST FAF TO MAP: 5.64 THLD: 5.64 4. MIN. ALT: CIMIX 3000, FEKLO 2600, UXREL/2.38 NM TO RW07 1560 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2600 GS ALT AT: FEKLO 2600 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS NOT CLEAR 8. MSA FROM: _____										MAG VAR: 6W		EPOCH YEAR: 1995					
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @					
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LPV DA	1184	1 1/2	419	1184	1 1/2	419	1184	1 1/2	419	1184	1 1/2	419					
LNAV/VNAV DA	1202	1 1/2	437	1202	1 1/2	437	1202	1 1/2	437	1202	1 1/2	437					
LNAV MDA	1280	1	515	1280	1	515	1280	1 3/8	515	1280	1 3/8	515					
CIRCLING	1380	1	614	1380	1	614	1420	1 3/4	654	1480	2 1/4	714					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: RWY 07 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.																	
CITY AND STATE  ATHENS/ALBANY, OH		ELEVATION: 766 TDZE: 765 AIRPORT NAME:  OHIO UNIVERSITY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, AMDT 2 9 NOVEMBER 2017						SUP:				
													AMDT: 1A				
													DATED 06/25/2015				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW07 (MAP)	1166 MSL (CA)	066.65	

1166 MSL	HOPAX (DF) (FO) (RNP 1.00)		3000
----------	----------------------------	--	------

TAA

	FROM	TO	ALT
1.	337/30 CW 157/30 (NOPT)	CIMIX (IF/IAF) (FB)	3000
2.	157/30 CW 247/30	NETKE (IAF) (FB)	3000
3.	247/30 CW 337/30	SOYLO (IAF) (FB)	3000

QUALITY  
25  
CHECKED

CITY AND STATE  
ATHENS/ALBANY, OH

ELEVATION: 766 TDZE: 765  
AIRPORT NAME:  
OHIO UNIVERSITY

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
RNAV (GPS) RWY 7, AMDT 2  
9 NOVEMBER 2017

SUP:	
AMDT:	1A
DATED:	06/25/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**FAS DATA BLOCK INFORMATION****DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KUNI
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	391233.6330N
LTP/FTP LONGITUDE	0821406.3755W
LTP/FTP ELLIPSOIDAL HEIGHT	+01984
FPAP LATITUDE	391317.2370N
FPAP LONGITUDE	0821226.3725W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1320
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

**CRC REMAINDER**

17C3F577

**ADDITIONAL PATH POINT RECORD INFORMATION**

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02325
FPAP ORTHOMETRIC HEIGHT	+02325

QUALITY  
25  
CHECKED

CITY AND STATE  ATHENS/ALBANY, OH	ELEVATION: 766 AIRPORT NAME:  OHIO UNIVERSITY	TDZE: 765   	FACILITY IDENTIFIER:  RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  RNAV (GPS) RWY 7, AMDT 2 9 NOVEMBER 2017	SUP:
					AMDT: 1A
					DATED: 06/25/2015