

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: VHP 14.43 DME								
VHP VORTAC			ZUTID/19.79 DME			020.74 / 19.79			2700		CLIMB TO 2700 DIRECT VHP VORTAC AND HOLD.								
OKK VORTAC (IAF)			YUKUL/29.79 DME (NOPT)			196.89 / 15.43			2700										
YUKUL/29.79 DME (IF)			ZUTID/19.79 DME			200.74 / 10.00 (VHP R-201)			2700										
										ADDITIONAL FLIGHT DATA: HOLD S, LT, 022.00 INBOUND. CHART FAS OBST: 1069 TREE 400425N/0861444W CHART 1169 TOWER 400829N/0861429W. CHART VDP AT 15.52 DME DISTANCE VDP TO THLD 1.09 NM. CHART CIRCLING ICON. 1136 AAO 400409N/0861130W ZUTID TO RW18: 3.04/51									
1. PT <u>R</u> SIDE OF COURSE <u>020.74</u> OUTBOUND <u>2700</u> FT WITHIN <u>10</u> MILES OF <u>ZUTID</u> (IAF)										MAG VAR: 1E EPOCH YEAR: 1965									
2.																			
3. FAC <u>200.74</u> FAF <u>ZUTID/19.79 DME</u> DIST FAF TO MAP <u> </u> THLD <u>5.36</u>																			
4. MIN. ALT <u>ZUTID 2700, VUVUY/16.68 DME 1620</u>																			
8. MSA FROM: <u>VHP VORTAC 3100</u>																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-18		1320	1	398	1320	1	398	1320	1 1/8	398	1320	1 1/8	398						
CIRCLING		1360	1	438	1380	1	458	1400	1 1/2	478	1480	2	558						
NOTES:																			
CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.									
CHART NOTE: DME REQUIRED.										<div>QUALITY 9 CHECKED</div>									
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE INDIANAPOLIS INTL ALTIMETER SETTING AND INCREASE ALL MDA 80 FT AND S-18 CATS C/D VISIBILITY 1/4 MILE.																			
(CONTINUED ON PAGE 2)																			
CITY AND STATE INDIANAPOLIS, IN		ELEVATION: 922 TDZE: 922 AIRPORT NAME: INDIANAPOLIS EXECUTIVE			FACILITY IDENTIFIER: VHP		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 18, AMDT 1D, 04/27/2017					SUP VOR/DME RWY 18 AMDT 1C DATE 11/10/2016							

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):**CHART NOTE: VDP NA WHEN USING INDIANAPOLIS INTL ALTIMETER SETTING.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT OKK VORTAC ON V305 NORTHBOUND.**

CITY AND STATE

INDIANAPOLIS, IN

ELEVATION: 922**TDZE: 922**

AIRPORT NAME:

INDIANAPOLIS EXECUTIVE

FACILITY
IDENTIFIER:

VHP

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 18, AMDT 1D, 04/27/2017SUP: **VOR/DME RWY 18**AMDT: **1C**DATED: **11/10/2016**