

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM			TO			COURSE AND DISTANCE				ALTITUDE		MAP: 5.19 NM AFTER CUEBE INT OR AT CFCJR.							
PWE VORTAC			CUEBE INT			266.23 / 24.87				3100		CLIMB TO 3000 THEN LEFT TURN DIRECT BIE VOR AND HOLD.							
BIE VOR			CUEBE INT			169.52 / 5.61				3000									
										ADDITIONAL FLIGHT DATA: HOLD N, RT, 165.00 INBOUND. CHART FAS OBST: 1681 TOWER 401549N/0964627W. CHART CIRCLING ICON. CUEBE TO RW36: 3.00/41. FAC CROSSES RWY C/L EXTENDED 2973 FT FROM THLD.									
1. PT <u>L</u> SIDE OF COURSE <u>169.52</u> OUTBOUND <u>3000</u> FT WITHIN <u>10</u> MILES OF <u>CUEBE INT</u> (IAF)																			
2.																			
3. FAC <u>349.52</u> FAF <u>CUEBE INT</u> DIST FAF TO MAP <u>5.19</u> THLD <u>5.19</u>																			
4. MIN. ALT <u>CUEBE INT 3000</u>																			
8. MSA FROM: <u>BIE VOR 3300</u>										MAG VAR: 7E EPOCH YEAR: 1980									
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-36		1940	3/4	633	1940	3/4	633	1940	1 3/8	633	1940	1 3/8	633						
CIRCLING		1940	1	616	1940	1	616	2000	2	676	2100	2 1/2	776						
NOTES:																			
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON PWE VORTAC AIRWAY RADIALS 216 CW 292.										@ CAT D 800-2 1/2									
CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-36 CAT A/B VISIBILITY TO 1 SM AND CAT C/D VISIBILITY TO 1 3/4 SM.																			
CITY AND STATE		ELEVATION: 1324			TDZE: 1307			FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:						SUP			
BEATRICE, NE		AIRPORT NAME:						BIE		VOR RWY 36, AMDT 10						AMDT 9A			
		BEATRICE MUNI								1 FEBRUARY 2018						DATE 02/05/2015			



**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.



CITY AND STATE

BEATRICE, NE

ELEVATION: 1324

TDZE: 1307

AIRPORT NAME:

BEATRICE MUNI

FACILITY
IDENTIFIER:

BIE

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 36, AMDT 10

1 FEBRUARY 2018

SUP:

AMDT: 9A

DATED: 02/05/2015