

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: ESC VOR/DME						
										CLIMB TO 2400 THEN RIGHT TURN DIRECT ESC VOR/DME AND HOLD.						
										ADDITIONAL FLIGHT DATA: HOLD S, RT, 351.00 INBOUND. CHART FAS OBST: 730 RIG 454309N/0870350W CHART CIRCLING ICON. FAC 34 FT L OF RWY C/L EXTENDED 3000 FT FROM THLD.						
1. PT <u>L</u> SIDE OF COURSE <u>171.00</u> OUTBOUND <u>2200</u> FT WITHIN <u>10</u> MILES OF <u>ESC VOR/DME</u> (IAF)																
2.																
3. FAC <u>351.00</u> FAF _____ DIST FAF TO MAP _____ THLD _____																
4. MIN. ALT _____																
8. MSA FROM: <u>ESC VOR/DME 360-090 3100, 090-360 2600</u>										MAG VAR: <u>0E</u> EPOCH YEAR: <u>1965</u>						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: <u>N A</u>		STANDARD @							
CATEGORY =====>		A			B			C			D			E		
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-01		1080	1	480	1080	1	480	1080	1 3/8	480	1080	1 3/8	480			
CIRCLING		1080	1	471	1080	1	471	1280	2	671	1480	2 3/4	871			
NOTES:																
CHART NOTE: STRAIGHT-IN RWY 1 NA AT NIGHT, CIRCLING RWY 1, 19 NA AT NIGHT.										@ NA WHEN LOCAL WEATHER NOT AVAILABLE.						
CHART NOTE: RWY 1 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.										@ CAT D 900-2 3/4						
CAUTION: MAGNETIC DISTURBANCES OF AS MUCH AS 14 DEGREES EXISTS AT GROUND LEVEL AT ESCANABA.																
(CONTINUED ON PAGE 2)																
CITY AND STATE ESCANABA, MI		ELEVATION: 609 TDZE: 600 AIRPORT NAME: DELTA COUNTY			FACILITY IDENTIFIER: ESC		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR RWY 1, ORIG-D 13 SEPTEMBER 2018					SUP VOR RWY 36 AMDT ORIG-C DATE 05/28/2015				

**VOR STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MARQUETTE ALTIMETER SETTING AND INCREASE ALL MDA 180 FEET AND INCREASE S-01 CAT C AND D VISIBILITY 1/2 SM, CIRCLING CAT C VISIBILITY 1/2 SM AND CAT D VISIBILITY 1/4 SM.

QUALITY
6
CHECKED

CITY AND STATE

ESCANABA, MI

ELEVATION: 609

TDZE: 600

AIRPORT NAME:

DELTA COUNTY

FACILITY
IDENTIFIER:

ESC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 1, ORIG-D

13 SEPTEMBER 2018

SUP: VOR RWY 36

AMDT: ORIG-C

DATED: 05/28/2015