

<b>US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION</b>				<b>RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, TITLE 14 CFR PART 97.33</b>				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		<b>RNP: DA</b>  <b>CLIMB TO 3000 DIRECT KIBKE AND ON TRACK 005.73 TO ALFOR AND HOLD.</b>  <b>ADDITIONAL FLIGHT DATA:</b> <b>HOLD N, LT, 179.19 INBOUND.</b> <b>DISTANCE TO THLD FROM 374 HAT: 1.02 NM.</b> <b>ROUTE TYPE QUALIFIER 1: F</b> <b>ROUTE TYPE QUALIFIER 2: S</b> <b>ROUTE TYPE: A, H</b> <b># TCH 423.6 MSL (DO NOT CHART)</b>					
SHEDD (IAF)		YIRSU (TF) (FB) (RNP 0.40)		151.64 / 20.61				5300							
VIDAS (IAF)		ZASUK (TF) (FB) (RNP 0.40)		217.38 / 9.72				5000							
ZASUK		RORBY (TF) (FB) (RNP 0.40)		217.26 / 9.72				3700							
VAUGN (IAF)		WOLKU (TF) (FB) (RNP 0.50)		067.20 / 7.03				3500							
SAGIN (IAF)		ZUMAG (TF) (FB) (RNP 0.30)		331.22 / 2.76				3100							
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. <b>PROFILE STARTS AT ICAVA</b> 3. FAC: <u>343.39</u> FAF: _____ DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: <b>ICAVA 1900</b> 5. DIST TO THLD FROM OM: <u>4.64</u> MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>1900</u> GS ALT AT: <b>ICAVA 1900</b> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>50.0</u> <b>34:1 IS NOT CLEAR</b> 8. MSA FROM: <b>RW34R 5900</b>															
										MAG VAR: <b>16E</b>			EPOCH YEAR: <b>2010</b>		
<b>MINIMUMS</b>															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A							
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
<b>AUTHORIZATION REQUIRED</b>															
RNP 0.30 DA	748	1	374	748	1	374	748	1	374	748	1	374			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -9C (16F) OR ABOVE 54C (130F). CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED. CHART NOTE: GPS REQUIRED. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SHEDD ON V536 WESTBOUND AND ON V23 NORTHBOUND. (CONTINUED ON PAGE 2)															
CITY AND STATE		ELEVATION: 374 TDZE: 374		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
EUGENE, OR		AIRPORT NAME:		MAHLON SWEET FIELD		RNAV (RNP) Z RWY 34R, AMDT 1 7 DECEMBER 2017				AMDT: <b>ORIG-B</b>					
										DATED <b>05/29/2014</b>					



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.		
RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33					
TERMINAL ROUTES, (CONT.):					
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
ZUMAG	SEYOK (TF) (FB) (RNP 0.30)	331.21 / 2.76	2700		
YIRSU (IF)	ZUBOL (TF) (FB) (RNP 0.40)	151.71 / 5.00	4600		
ZUBOL	RORBY (RF) (FB) (RNP 0.40)	(5.25 NM RADIUS CW (CFVHV))/6.00	3700		
RORBY (IF)	WOLRI (RF) (FB) (RNP 0.40)	(5.25 NM RADIUS CW (CFVHV))/8.37	2600		
WOLRI	ICAVA (RF) (FB) (RNP 0.40)	(5.25 NM RADIUS CW (CFVHV))/3.21	1900		
WOLKU (IF)	HABGI (RF) (FB) (RNP 0.50)	(4.26 NM RADIUS CCW (CFFSV))/3.12	2800		
HABGI	ICAVA (RF) (FB) (RNP 1.00)	(4.26 NM RADIUS CCW (CFFSV))/3.12	1900		
SEYOK (IF)	ICAVA (TF) (FB) (RNP 1.00)	343.39 / 5.56	1900		
ICAVA (FAF)	RW34R (MAP) (TF) (FB) (RNP 0.30)	343.39 / 4.64			
RW34R (MAP)	748 MSL (CA)	343.40			
748 MSL	KIBKE (DF) (FB) (RNP 1.00)				
KIBKE	ALFOR (TF) (FO) (RNP 1.00)	005.73/6.04	3000		
NOTES, (CONT.): CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT VIDAS ON V121 EASTBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT VAUGN ON V495 SOUTHBOUND AND V121 SOUTHWEST BOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SAGIN ON V23 SOUTHBOUND. CHART PLANVIEW NOTE ADJACENT TO SHEDD: RF REQUIRED. CHART PLANVIEW NOTE ADJACENT TO VIDAS: RF REQUIRED. CHART PLANVIEW NOTE ADJACENT TO VAUGN: RF REQUIRED. CHART PLANVIEW NOTE AT SHEDD: (RNP 0.40).					
CITY AND STATE EUGENE, OR	ELEVATION: 374 AIRPORT NAME: MAHLON SWEET FIELD	TDZE: 374	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 34R, AMDT 1 7 DECEMBER 2017	SUP: AMDT: ORIG-B DATED: 05/29/2014

QUALITY  
18  
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION RNAV (RNP) - STANDARD, INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
CHART PLANVIEW NOTE AT VIDAS: (RNP 0.40). CHART PLANVIEW NOTE AT VAUGN: (RNP 0.50). CHART PLANVIEW NOTE AT SAGIN: (RNP 0.30). CHART PROFILE NOTE: SEE PLANVIEW FOR MULTIPLE IF LOCATIONS.				
<div>QUALITY 18 CHECKED</div>				
CITY AND STATE EUGENE, OR	ELEVATION: 374 AIRPORT NAME: MAHLON SWEET FIELD	TDZE: 374	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 34R, AMDT 1 7 DECEMBER 2017
				SUP:
				AMDT: ORIG-B
				DATED: 05/29/2014