

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW09							
PHK VOR/DME		LMORE (TF) (FB) (RNP 2.00)		131.55 / 17.66				2600		CLIMBING RIGHT TURN TO 2000 DIRECT UGLEE AND HOLD. DO NOT EXCEED 210 KIAS UNTIL TURN COMPLETION.							
LMORE (IAF)		ZOTUB (NOPT) (TF) (FB) (RNP 1.00)		102.08 / 7.82				2600									
ARKES (IAF)		ZOTUB (NOPT) (TF) (FB) (RNP 1.00)		086.89 / 7.51				2600		ADDITIONAL FLIGHT DATA: HOLD S, RT, 009.00 INBOUND. CHART FAS OBST: 158 TREE 263549N/0800521W CHART: 1314 TOWER 263521N/0801243W KUVBE TO RW09: 3.00/45.1. CHART CIRCLING ICON. FAC CROSSES RWY 09 THLD.							
ZOTUB (IF/IAF)		KUVBE (TF) (FB) (RNP 1.00)		097.87 / 3.43				2200									
KUVBE (FAF)		YEGUP/2.60 NM TO RW09 (TF) (RNP 0.30)		097.89 / 4.13													
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. HOLD W ZOTUB, RT, 097.87 INBOUND, 2600 FT. IN LIEU OF PT (IAF)																	
3. FAC: 097.89 FAF: KUVBE DIST FAF TO MAP: 6.73 THLD: 6.73																	
4. MIN. ALT: ZOTUB 2600, KUVBE 2200, YEGUP/2.60 NM TO RW09 880																	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: _____ TCH: _____																	
8. MSA FROM: RW09 2600																	
MAG VAR: 6W EPOCH YEAR: 2010																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X							
CATEGORY =====>		A			B			C			D			E			
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
CIRCLING		460	1	446	580	1	566	660	1 3/4	646		NA					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ARKES ON V159 NORTHBOUND. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON PHK VOR/DME AIRWAY RADIALS 115 CW 211. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. (CONTINUED ON PAGE 2)																	
CITY AND STATE WEST PALM BEACH, FL		ELEVATION: 14 TDZE: AIRPORT NAME: PALM BEACH COUNTY PARK			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG-A 27 APRIL 2017					SUP: AMDT: DATED 08/22/2013				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
YEGUP/2.60 NM TO RW09	RW09 (MAP) (TF) (FO) (RNP 0.30)	097.89 / 2.60	
RW09 (MAP)	414 MSL (CA)	097.89	
414 MSL	UGLEE (DF) (FO) (RNP 1.00)		2000

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING IS NOT RECEIVED, USE PALM BEACH INTL ALTIMETER SETTING:

INCREASE ALL MDA 20 FEET.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: PROCEDURE NA AT NIGHT.

CITY AND STATE

WEST PALM BEACH, FL

ELEVATION: 14

TDZE:

AIRPORT NAME:

PALM BEACH COUNTY PARK

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS)-A, ORIG-A

27 APRIL 2017

SUP:

AMDT:

DATED:

QUALITY
4
ORIG
CHECKED
08/22/2013