

DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION - FLIGHT STANDARDS SERVICE
DEPARTURE PROCEDURES/TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH → ☐ AAT ☐ ATA ☐ ALPA ☒ AOPA ☒ NBAA ☒ APA ☒ OTHER (Specify) LBF FSS, ZDV, NE STATE AERO.

TAKEOFF MINIMUMS:

RWYs 3, 14, 21 STANDARD
 2 300-1 or STANDARD
 minimum climb of 300'
 per NM to 2800.

TAKEOFF OBSTACLES:

RWY 32: 2754 Water Tower 405625/1000900

*Concurrent with NDB RWY 32, Amdt. 1.

DEVELOPED BY <i>James G. Duea</i>		APPROVED BY <i>Robert J. Marlott</i>	
SIGNATURE James G. Duea Procedures Specialist	DATE 12/29/80 FIFO	SIGNATURE Robert J. Marlott, Manager, MSP FIFO	DATE 12/29/80
CITY AND STATE Gothenburg, NE	AIRPORT Gothenburg Muni	EFFECTIVE DATE * 4/16/81	AMDT. NO. 1

8260-15