

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW07 CLIMBING LEFT TURN TO 3000 DIRECT BAARN AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, LT, 256.02 INBOUND. FAS OBST: 1339 AAO 401550N/0762234W ZIKMO TO RW07: 3.00/40. CHART LANCASTER ASOS.											
WILEN (IF/IAF)	ZIKMO (FB)	059.18 / 6.11	2200												
ZIKMO (FAF)	RW07 (MAP) (FO)	068.02 / 5.06	3000												
RW07 (MAP)	950 MSL	068.02													
950 MSL	BAARN (FO)														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT WILEN 3. FAC: 068.02 FAF: ZIKMO DIST FAF TO MAP: 5.06 THLD: 5.06 4. MIN. ALT: WILEN 3000, ZIKMO 2200 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW07 3100				MAG VAR: 12W EPOCH YEAR: 2010											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A X												
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	1640	1 1/4	1093	1640	1 1/2	1093		NA			NA				
CIRCLING	1640	1 1/4	1090	1640	1 1/2	1090		NA			NA				
NOTES: CHART NOTE: USE LANCASTER ALTIMETER SETTING; WHEN NOT RECEIVED, USE READING ALTIMETER SETTING AND INCREASE ALL MDA 40 FT. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. (SEE FORM 8260-10)															
CITY AND STATE LEBANON, PA		ELEVATION: 550 THRE: 547 AIRPORT NAME: KELLER BROTHERS		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 31 MAY 2012				SUP: AMDT: NONE DATED					

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WILEN ON V210 NORTHWEST BOUND.

QUALITY
CHECKED

CITY AND STATE
LEBANON, PA

ELEVATION: 550 THRE: 547
AIRPORT NAME:
KELLER BROTHERS

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 7, ORIG
31 MAY 2012

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

ELEVATION: 550 THRE: 547
AIRPORT NAME:
KELLER BROTHERS

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 7, ORIG
31 MAY 2012

SUP:	
AMDT:	NONE
DATED:	