

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HUNTSVILLE INTL - CARL T JONES FIELD
ALTIMETER SETTING AND INCREASE ALL DA 142 FT AND ALL MDA 140 FT; INCREASE LPV ALL CATS VISIBILITY
1/4 MILE, LNAV/VNAV ALL CATS VISIBILITY 3/8 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	258/30 CW 078/30 (NOPT)	UWNED (IF/IAF) (FB)	3800
2.	078/30 CW 168/30	ZIDID (IAF) (FB)	3800
3.	168/30 CW 258/30	ZUPNA (IAF) (FB)	3800

CITY AND STATE

LAWRENCEBURG, TN

ELEVATION: 936

THRE: 927

AIRPORT NAME:

LAWRENCEBURG-LAWRENCE COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG

3 APRIL 2014

SUP:

AMDT: NONE

DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	2M2
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	351339.4295N
LTP/FTP LONGITUDE	0871521.5815W
LTP/FTP ELLIPSOIDAL HEIGHT	+02549
FPAP LATITUDE	351506.2180N
FPAP LONGITUDE	0871546.9045W
THRESHOLD CROSSING HEIGHT (TCH)	00060.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.20
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

0E741DF4

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+02825
FPAP ORTHOMETRIC HEIGHT	+02825

CITY AND STATE

LAWRENCEBURG, TN

ELEVATION: 936

THRE: 927

AIRPORT NAME:

LAWRENCEBURG-LAWRENCE COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 35, ORIG

3 APRIL 2014

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 2M2 K7FR35	AUWNED	010UWNEDK7EA0EE	AR	HF			34760040	+	03800	18000		A	JS
SUSAP 2M2 K7FR35	AZIDID	010ZIDIDK7EA0E	A	IF						18000		A	JS
SUSAP 2M2 K7FR35	AZIDID	020UWNEDK7EA0EE	B	010TF			25770080	+	03800			A	JS
SUSAP 2M2 K7FR35	AZUPNA	010ZUPNAK7EA0E	A	IF						18000		A	JS
SUSAP 2M2 K7FR35	AZUPNA	020UWNEDK7EA0EE	B	010TF			07750080	+	03800			A	JS
SUSAP 2M2 K7FR35	R	010UWNEDK7EA0E	I	IF				+	03800	18000		A	JS
SUSAP 2M2 K7FR35	R	020YITUTK7EA1E	F	051TF			34760080	+	02600			A	JS
SUSAP 2M2 K7FR35	R	020YITUTK7EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP 2M2 K7FR35	R	021JOMVUK7EA0E	S	031TF			34760024	V	0180001802		-320	A	JS
SUSAP 2M2 K7FR35	R	030RW35 K7PGOGY	M	031TF			34760024		00987		-320	A	JS
SUSAP 2M2 K7FR35	R	040	0	M	CA		3476	+	01293			A	JS
SUSAP 2M2 K7FR35	R	050WABOLK7EA0EY		DF				+	03700			A	JS
SUSAP 2M2 K7FR35	R	060WABOLK7EA0EE	R	HM			16750040	+	03700			A	JS

[illegible][illegible]FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	UWNED	UWNED	010	IAF	HF	R	FO		347.6 (346.6T)	004.0	AA 03800	
	ZIDID	ZIDID	010	IAF	IF		FB					
	ZIDID	UWNED	020		TF		FB	1.0	257.7 (256.7T)	008.0	AA 03800	
	ZUPNA	ZUPNA	010	IAF	IF		FB					
	ZUPNA	UWNED	020		TF		FB	1.0	077.5 (076.5T)	008.0	AA 03800	
		UWNED	010	FACF	IF		FB				AA 03800	
		YITUT	020	FAF	TF		FB	0.5	347.6 (346.6T)	008.0	AA 02600	
		JOMVU	021	SDF	TF		FB	0.3	347.6 (346.6T)	002.4	AA 01800	GS 01802
		RW35	030	MAP	TF		FO	0.3	347.6 (346.6T)	002.4	AT 00987	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		347.6 (346.6T)		AA 01293	
	WABOL	050		DF		FO				AA 03700	
	WABOL	060		HM	R	FO		167.5 (166.5T)	004.0	AA 03700	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	JOMVU	N351119.16	W0871440.69	N3511.319	W08714.678
	UWNED	N350114.33	W0871144.82	N3501.239	W08711.747
	WABOL	N352618.50	W0871903.55	N3526.308	W08719.059
	YITUT	N350901.94	W0871400.72	N3509.032	W08714.012
	ZIDID	N350305.58	W0870216.15	N3503.093	W08702.269
	ZUPNA	N345922.34	W0872113.06	N3459.372	W08721.218
	RW35	N351339.43	W0871521.58	N3513.657	W08715.360

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW35	00927	60

CITY AND STATE
LAWRENCEBURG, TN

ELEVATION: **936** THRE: **927**
 AIRPORT NAME:
LAWRENCEBURG-LAWRENCE COUNTY

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 35, ORIG
3 APRIL 2014

SUP:
 AMDT: **NONE**
 DATED: