

U.S. Department
of Transportation

800 Independence Ave., S.W.
Washington, D.C. 20591

**Federal Aviation
Administration**

Transmittal Letter 17-17

June 30, 2017

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
17-Aug-17	MS	Greenwood	Greenwood-Leflore	7/0298	6/9/17	ILS OR LOC RWY 18, Amdt 8A

AIRAC Date: 17 AUGUST 2017

FDC 7/0298 GWO IAP GREENWOOD-LEFLORE, Greenwood, MS. ILS OR LOC RWY 18, AMDT 8A... CHART TDZE 145, DELETE THRE 145. CHART APT ELEV 162. CHART CIRCLING ICON. CIRCLING CAT A/B HAA 598, CAT C MDA 1000/HAA 838, CAT D MDA 1120/HAA 958, VIS CAT C 2-1/2, CAT D 3. JULTU FIX MINIMUMS CIRCLING CAT A/B HAA 598, CAT C MDA 1000/HAA 838, CAT D MDA 1120/HAA 958, VIS CAT C 2-1/2, CAT D 3. CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: RWY 5, 23, 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: CIRCLING RWY 5, 23, 27 NA AT NIGHT. DELETE NOTE: CIRCLING TO RWY 5/23/27 NA AT NIGHT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREENVILLE ALTIMETER SETTING: INCREASE DA TO 580 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 120 FEET AND VISIBILITY S-LOC 18 CAT C/D 1/4 SM AND CIRCLING CAT C 1/2 SM AND JULTU FIX MINIMUMS S-LOC 18 CAT C/D 1/4 SM AND CIRCLING CAT C 1/2 SM. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GREENVILLE ALTIMETER SETTING AND INCREASE DA TO 579 FT AND ALL VISIBILITIES 1/4 MILE; INCREASE ALL MDA 120 FT AND VISIBILITY CAT C AND D 1/4 MILE, CIRCLING VISIBILITY CAT C AND D 1/2 MILE. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 18 CAT A/B VISIBILITY TO 1 SM, AND CAT C/D TO 1 3/8 SM, AND JULTU FIX MINIMUMS S-LOC 18 ALL CATS TO 1 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE S-LOC 18 CAT A AND B VISIBILITY 1/4 MILE, S-LOC 18 CAT C AND D VISIBILITY 3/8 MILE AND JULTU FIX MINIMUMS S-LOC 18 ALL CATS VISIBILITY 1/4 MILE. CHART NOTE: FOR INOPERATIVE ALS WHEN USING GREENVILLE ALTIMETER SETTING, INCREASE S-ILS 18 ALL CATS VISIBILITY TO 1 1/2 SM, AND S-LOC 18 CAT A/B TO 1 SM, AND JULTU FIX MINIMUMS S-LOC 18 CAT A/B TO 1 SM, AND CAT C/D TO 1 3/8 SM. DELETE NOTE: FOR INOPERATIVE MALSR; WHEN USING GREENVILLE ALTIMETER SETTING, INCREASE S-ILS 18 ALL CATS VISIBILITY 1/2 MILE, S-LOC CAT A AND B VISIBILITY 1/4 MILE AND JULTU FIX MINIMUMS CAT A AND B VISIBILITY 1/4 AND CAT C AND D VISIBILITY 3/8 MILE. ALTERNATE MINIMUMS: S-ILS STANDARD

EXCEPT CAT C 900-2 1/2, CAT D 1000-3, LOC STANDARD EXCEPT CAT C 900-2 1/2, CAT D 1000-3, ILS AND LOC NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS ILS OR LOC RWY 18, AMDT 8B. 1705041504-PERM