U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RDU VORTAC (IF)	DAANY/RDU 9.00 DME	289.68 / 9.00	2100

MISSED APPROACH

MAP: EXTER/RDU 14.08 DME

CLIMB TO 2300 THEN CLIMBING LEFT TURN TO 3100 ON HEADING 180 AND ON RDU VORTAC R-279 TO CHAPL INT/RDU 13.00 DME AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD W, RT, 099.00 INBOUND.
CHART FAS OBST: 751 TANK 355715N/0790256W
DAANY TO RW27: 2.91/40.
CHART: MAX 6000 AT RDU VORTAC

1. PT R SIDE OF COURSE 109.68 OUTBOUND 3000 FT WITHIN 10 MILES OF RDU VORTAC (IAF)
2.
3. FAC 289.68 FAF DAANY/RDU 9.00 DME DIST FAF TO MAP THLD 5.08
4. MIN. ALT RDU VORTAC 3000, DAANY 2100
8. MSA FROM: RDU VORTAC 3400

MAG VAR: 4W EPOCH YEAR: 1965

MINIMUMS

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT ALTERNATE: N A STANDARD

CATEGORY =====>	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA
S-27	1060	1	568	1060	1	568	1060	1 5/8	568	1060	1 5/8	568			
CIRCLING	1100	1	588	1120	1	608	1120	1 3/4	608	1120	2	608			

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.
CHART PLANVIEW NOTE: NOPT FOR ARRIVAL ON RDU VORTAC AIRWAY RADIALS 020 CW 189.
CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.
CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

QUALITY CHECKED

CITY AND STATE	ELEVATION: 512 THRE: 492	FACILITY IDENTIFIER:	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP
CHAPEL HILL, NC	AIRPORT NAME: HORACE WILLIAMS	RDU	VOR/DME RWY 27, AMDT 1A 12 DECEMBER 2013	AMDT 1
				DATE 05/10/2007