

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM	TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW34 CLIMB TO 2300 DIRECT HEVAB AND ON TRACK 053.55 TO CMK VOR/DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD E, RT, 256.76 INBOUND. CHART FAS OBST: 585 TOWER 410401N/0734143W DISTANCE TO THLD FROM 322 HAT: 0.91 NM. CHART VDP AT 1.27 NM TO RW34* *LNAV ONLY. WAAS CHANNEL # 99410 REFERENCE PATH ID: W34A CHART CIRCLING ICON. LTP HAE: 85.1 M						
BDR VOR/DME	DABVE (TF) (FB) (RNP 2.00)			247.68 / 12.00			3000								
DABVE	TUGME (TF) (FB) (RNP 2.00)			249.63 / 8.77			3000								
HAARP	MOISE (TF) (FB) (RNP 2.00)			141.82 / 5.24			3000								
RYMES	MOISE (TF) (FB) (RNP 2.00)			184.00 / 7.90			3000								
MOISE	TUGME (TF) (FB) (RNP 2.00)			192.00 / 5.84			3000								
(SEE FORM 8260-10)															
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT JETAX 3. FAC: <u>342.94</u> FAF: <u>ISLET</u> DIST FAF TO MAP: <u>3.00</u> THLD: <u>3.00</u> 4. MIN. ALT: <u>JETAX 2000, ISLET 1400</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>1400</u> GS ALT AT: <u>ISLET 1400</u> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>55.3</u> 34:1 IS NOT CLEAR 8. MSA FROM: <u>RW34 2900</u>															
										MAG VAR: 13W EPOCH YEAR: 2020					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	723	6000	322	723	6000	322	723	6000	322	723	6000	322			
LNAV/VNAV DA	780	1 1/2	379	780	1 1/2	379	780	1 1/2	379	780	1 1/2	379			
LNAV MDA	840	5000	439	840	5000	439	840	6000	439	840	1 1/2	439			
CIRCLING	980	1	541	980	1	541	1080	1 3/4	641	1200	2 1/2	761			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). @ CAT D 800-2 1/2 CHART NOTE: CIRCLING RWY 11, 29 NA AT NIGHT. CHART NOTE: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: DME/DME RNP-0.3 NA. (CONTINUED ON PAGE 2)															
CITY AND STATE			ELEVATION: 439 TDZE: 401			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:		
WHITE PLAINS, NY			AIRPORT NAME:						RNAV (GPS) Y RWY 34, AMDT 3C				AMDT: 3B		
			WESTCHESTER COUNTY						7 DECEMBER 2017				DATED 05/30/2013		



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
TUGME (IAF)	JETAX (TF) (FB) (RNP 1.00)	253.05 / 5.00	2000
JETAX (IF)	ISLET (TF) (FB) (RNP 1.00)	342.99 / 6.51	1400
ISLET (FAF)	RW34 (MAP) (TF) (FO) (RNP 0.30)	342.94 / 3.00	
RW34 (MAP)	723 MSL (CA)	342.94	
723 MSL	HEVAB (DF) (FB) (RNP 1.00)		
HEVAB	CMK VOR/DME (TF) (FO) (RNP 1.00)	053.55 / 11.99	2300

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RYMES ON V483 NORTHBOUND AND ON V123 NORTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON BDR VOR/DME AIRWAY RADIALS 212 CW 248.

QUALITY
25
CHECKED

CITY AND STATE
WHITE PLAINS, NY

ELEVATION: 439 TDZE: 401
AIRPORT NAME:
WESTCHESTER COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) Y RWY 34, AMDT 3C
7 DECEMBER 2017

SUP:
AMDT: 3B
DATED: 05/30/2013

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KHPN
RUNWAY	RW34
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W34A
LTP/FTP LATITUDE	410336.0020N
LTP/FTP LONGITUDE	0734205.0480W
LTP/FTP ELLIPSOIDAL HEIGHT	+00851
FPAP LATITUDE	410453.1455N
FPAP LONGITUDE	0734304.0960W
THRESHOLD CROSSING HEIGHT (TCH)	00055.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0752
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 359C23A9

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K6
LTP ORTHOMETRIC HEIGHT	+01158
FPAP ORTHOMETRIC HEIGHT	+01158

QUALITY
25
CHECKED

CITY AND STATE WHITE PLAINS, NY	ELEVATION: 439 AIRPORT NAME: WESTCHESTER COUNTY	TDZE: 401 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 34, AMDT 3C 7 DECEMBER 2017	SUP:
				AMDT: 3B
				DATED: 05/30/2013