

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV/VNAV: DA LNAV: RW35 CLIMB TO 5000 DIRECT EGIPT AND ON TRACK 310.95 TO ZOBLA AND ON TRACK 259.02 TO AMERY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NW, RT, 113.67 INBOUND. CHART FAS OBST: 144 TREE 194341N/1560219W CHART VDP AT 1.67 MILES TO RW35* *LNAV ONLY.											
KOA VORTAC	HASOG (FO)	174.55 / 11.66	2200												
UJGEM (IAF)	HASOG (NOPT) (FB)	083.74 / 12.03	2000												
HASOG (IF/IAF)	HOXLY (FB)	353.81 / 7.00	1700												
HOXLY (FAF)	RW35 (MAP) (FO)	353.82 / 5.03													
RW35 (MAP)	447 MSL	353.82													
447 MSL	EGIPT (FB)														
EGIPT	ZOBLA (FB)	310.95 / 9.73													
ZOBLA	AMERY (FO)	259.02 / 14.99	5000												
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD S HASOG, LT, 353.81 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>353.82</u> FAF: <u>HOXLY</u> DIST FAF TO MAP: <u>5.03</u> THLD: <u>5.03</u> 4. MIN. ALT: <u>HASOG 2000, HOXLY 1700</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u>1700</u> GS ALT AT: <u>HOXLY 1700</u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u>3.00</u> TCH: <u>60.0</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW35 14900</u>				MAG VAR: 11E EPOCH YEAR: 1985											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A		STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV/VNAV DA	540	1 5/8	503	540	1 5/8	503	540	1 5/8	503	540	1 5/8	503	540	1 5/8	503
LNAV MDA	640	1	603	640	1	603	640	1 3/4	603	640	1 3/4	603	640	1 3/4	603
CIRCLING	640	1	593	640	1	593	640	1 3/4	593	640	2	593	640	2	593
NOTES: CHART NOTE: CIRCLING NA EAST OF RWY 17-35. CHART NOTE: WAAS VNAV NA CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -5C (23F) OR ABOVE 43C (109F). CHART NOTE: DME/DME RNP-0.3 NA. (SEE FORM 8260-10)															
CITY AND STATE		ELEVATION: 47 THRE: 37		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:					
KAILUA/KONA, HI		AIRPORT NAME:		KONA INTL AT KEAHOLE		RNAV (GPS) Z RWY 35, AMDT 1, 08/25/2011				AMDT: ORIG-B					
						25 AUG 2011				DATED 11/25/2004					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGS1 AND RNAV GLIDEPATH NOT COINCIDENT.

CHART IN PLANVIEW: RADAR REQUIRED FOR ARRIVALS AT UJGEM.

QUALITY
4
CHECKED

CITY AND STATE

KAILUA/KONA, HI

ELEVATION: 47

THRE: 37

AIRPORT NAME:

KONA INTL AT KEAHOLE

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Z RWY 35, AMDT 1, 08/25/2011

25 AUG 2011

SUP:

AMDT: ORIG-B

DATED: 11/25/2004

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
4
CHECKED

CITY AND STATE KAILUA/KONA, HI	ELEVATION: 47 THRE: 37 AIRPORT NAME: KONA INTL AT KEAHOLE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 35, AMDT 1, 08/25/2011 25 AUG 2011	SUP:
				AMDT: ORIG-B
				DATED: 11/25/2004

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE KAILUA/KONA, HI	ELEVATION: 47 THRE: 37 AIRPORT NAME: KONA INTL AT KEAHOLE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) Z RWY 35, AMDT 1, 08/25/2011 25 AUG 2011	SUP:
				AMDT: ORIG-B
				DATED: 11/25/2004