

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME OR TACAN STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH										
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: ZADEK/UNZ 2.50 DME FIX									
HAMAL/7.00 DME CCW (IAF)			FLAKE/UNZ 7.00 DME (NOPT)			7.00 DME ARC (UNZ LR-259)			2600		CLIMB TO 2600 THEN RIGHT TURN ON UNZ VORTAC R-242 TO FLAKE/7.00 DME AND HOLD.									
ZEEKE/7.00 DME CW (IAF)			FLAKE/UNZ 7.00 DME (NOPT)			7.00 DME ARC (UNZ LR-225)			2600											
FLAKE/UNZ 7.00 DME (IF/IAF)			CUDID/UNZ 1.50 DME			061.83 / 5.50 (UNZ LR-242)			2000											
										ADDITIONAL FLIGHT DATA: CHART FAS OBST: 450 TOWER 132653N/1444522E. CHART 1190 TOWER 132559N/1444246E. CHART UNZ R-343 AT HAMAL. CHART UNZ R-169 AT ZEEKE. CHART CIRCLING ICON. MOMRE TO RW06L: 3.71/72.9 CHART IN PROFILE: UNZ VORTAC. CHART PLANVIEW NOTE: DME REQUIRED.										
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 2E EPOCH YEAR: 2000										
2. HOLD SW FLAKE, RT, 061.83 INBOUND, 2600 FT. IN LIEU OF PT (IAF)																				
3. FAC 061.83 FAF CUDID/UNZ 1.50 DME DIST FAF TO MAP _____ THLD 4.80																				
4. MIN. ALT FLAKE 2600, CUDID 2000, MOMRE/UNZ 1.30 DME 1100																				
8. MSA FROM: UNZ VORTAC 2600																				
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD								
CATEGORY =====>		A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA					
S-06L	760	1/2	504	760	1/2	504	760	1	504		NA									
CIRCLING	860	1	555	860	1	555	940	1 3/4	635		NA									
NOTES: CHART NOTE: CIRCLING NA SOUTHEAST OF RWY 6R-24L. CHART NOTE: DME REQUIRED. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}). CHART NOTE: FOR INOPERATIVE ALS, INCREASE CAT C VISIBILITY TO 1 3/8 SM.																				
CITY AND STATE GUAM, GU		ELEVATION: 305 AIRPORT NAME:  GUAM INTL		TDZE: 256		FACILITY IDENTIFIER: UNZ		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR OR TACAN RWY 6L, ORIG-F 24 MAY 2018				SUP VOR/DME OR TACAN RWY 6L		AMDT ORIG-E						
												DATE 12/15/2011								

