

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2.	HOLD W MVC VORTAC, RT, 095.19 INBOUND, 2000 FT. IN LIEU OF PT (IAF)				
3. FAF	095.19	FAF DINGS/10.50 DME	DIST FAF TO MAP		THLD 5.37
4. MIN. ALT	MVC VORTAC 2000, DINGS 2000, REBAE/13.30 DME 1080				
8. MSA FROM:	MVC VORTAC 2000				

EPOCH YEAR:1965

[illegible]

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

FAA FORM 8260-5 / December 2002 (computer generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

**VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - FAR PART 97.23**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

SETTING AND INCREASE ALL MDAS 100 FEET, S-10 VISIBILITY CAT C/D 1/4 MILE, CIRCLING VISIBILITY CAT C 1/4 AND CAT D 1/2 MILE.

CITY AND STATE
EVERGREEN, AL

ELEVATION: 259 TDZE: 259
AIRPORT NAME:
MIDDLETON FIELD

FACILITY
IDENTIFIER:
MVC

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
VOR/DME RWY 10, AMDT 3
APR 10 2008

SUP: VOR/DME OR GPS
RWY 10
AMDT: 2A
DATED: 04/14/1999

